

Soft Tinned Copper Wire

pro-POWER



Description

The TCW24 500G from Pro Power is a soft, solid tinned copper wire desirable for connectivity and easy soldering purposes. The surface finish shall be bright, clean and free from harmful defects. Conforms to BS EN 13602:2013 CW004A standards.

Specifications

Conductor material	: Soft, solid tinned copper
Colour	: Bright to dull silvery grey
Wire size	: 24 SWG
Diameter	: 0.56mm
Melting point	: 1083°C (Copper), 232°C (Tin)
Tolerance	: Inches $\pm 1\%$
Elongation	: 22% Minimum
Resistance	: 89.55 Ω / km
Yield	: 2.19kg / 1000m

Part Number Table

Description	Reel Length	Part Number
Wire, Copper Tinned, 24 SWG	230m	TCW24 500G

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-POWER is the registered trademark of Premier Farnell Limited 2019.

Newark.com/exclusive-brands
Farnell.com/exclusive-brands
Element14.com/exclusive-brands

pro-POWER