

ENGLISH

Datasheet

RS Pro Gas, Liquid Gauge Pressure Switch 0 to 10bar, Analogue, 10 to 30 V dc, G1/4 process connection RS Stock No: 518-4434



Product Details

RS Pro gas and liquid gauge pressure switch has a pressure range of 0 to 10 bar. It comes with 10 to 30 V dc supply voltage and G1/4 process connection. It works according to the thick-film DMS measuring principle. It has a stainless steel housing and M12 connector pin.

Features and Benefits

- Operating temperature range of -20 to +125°C
- Pressure transducer for relative pressure
- Suitable for liquid and gaseous media
- Analogue output type



ENGLISH

Specifications:

| Accuracy | ≤0.5% |
|-------------------------------|-----------------|
| Analogue Output | 4 to 20 mA |
| Electrical Connection | M12 Connector |
| Housing Material | Stainless Steel |
| IP Rating | IP67 |
| Maximum Operating Temperature | +125°C |
| Maximum Pressure Reading | 10 bar |
| Media Measured | Gas, Liquid |
| Minimum Operating Temperature | -20°C |
| Minimum Pressure Reading | 0 bar |
| Mounting Type | Not Front-Flush |
| Output Type | Analogue |
| Pressure Range | 0 to 10 bar |
| Pressure Reading Type | Gauge |
| Process Connection | G 1/4 |
| Response Time | ≤3 ms |
| Supply Voltage | 10 to 30 V dc |