



Product datasheet

ENGLISH

Slip Resistant Black Tape (Tile format)

- Size: 140mm x 140mm
- Thickness: $1.0 \pm 0.05\text{mm}$
- Grit Size: 60 grit
- Abrasive grit 'anti-slip' products with self-adhesive backing.
Gripfoot Tiles (square) are ideal for increasing safety on smooth, tiled floors.
Provides additional grip underfoot on smooth surfaces.
Hard wearing and easy to install.
- Colour: Black
- Pack of 10

RS Code: 7621512

Conforms to Slip Resistant Test EN 13552 Category R13.





Gripfoot

Grit Tape, Cleats and Tiles for Slip-Resistance

- Abrasive grit 'anti-slip' products with self-adhesive backing available in tapes, cleats and tiles.
- Provides additional grip underfoot on smooth surfaces.
- Hard wearing and easy to install
- Gripfoot Tape – versatile for floor surfaces, machinery, vehicles and marine use.
- Gripfoot Cleats (rectangular) are designed for use on steps and stairs.
- Gripfoot Tiles (square) are ideal for increasing safety on smooth, tiled floors.
- Hazard version (tape only) in yellow/black provides high visibility in darkness or low light conditions.
- Conforms to Slip Resistant Test EN 13552 Category R13.

Dimensions (m.)	Weight Kg	Packaging Dimensions (cm.)	Packaging Type	Packaging Volume (m.)	Packaging Quantity	Colour	Part Code
25mm x 18.3m	0.40	15 x 16 x 2.5	Jiffy Bag	1	27	Black	
50mm x 18.3m	0.85	20 x 26 x 6	Jiffy Bag	1	27	Black	
102mm x 18.3m	1.55	20 x 33 x 11	Jiffy Bag	1	27	Black	7621500
152mm x 18.3m	2.35	20 x 20 x 16	Jiffy Bag	1	27	Black	
140mm x 140mm	0.75	18 x 66 x 1.5	Jiffy Bag	10	N/A	Black	7621512
152mm x 610mm	0.15	18 x 20 x 1.5	Jiffy Bag	10	N/A	Black	7612516
50mm x 18.3m			Jiffy Bag			Black/Yellow	

Material: Abrasive grit consisting of aluminium oxide bonded to a polymer substrate. Solvent based acrylic emulsion adhesive backing. Product supplied with a moisture resistant release liner.

Typical Applications: Suitable for stairs, ladders, ramps, walkways, vehicles and boats.

Surface Finish: Grit

Grit size: 46 grit

Thickness: 1.0+ ± 0.05mm

Resistance to Chemicals: N/A

Environmental Resistance: Suitable for indoor and outdoor environments

UV Resistance: Yes

Installation Method: Pressure sensitive self-adhesive tape

Product Performance: Conforms to slip resistance test EN13552 Category R13

Adhesion Properties

Rolling Ball Tack 20cm

Shear Resistance 24 hrs (1" X 1" @ 1 kg)

Coating Thickness 0.05 mm

Solvent Residual >0.5 %

Adhesion 2.5 kg/1"



Release Force 13 g/m²
Dry Coating Weight 37 g/m²
Operation Temperature 10 °c +
Safe Temperature Range -10 °c to +60 °c
Adhesive Type Acrylic Adhesive

Web Properties

Property	Grit Carrier Substrate	Release Liner
Web Type	PVC Film	Release Liner
Basic Weight	181 g/m ²	120 g/m ²
Thickness	0.15 mm	0.185 mm
Tensile Strength	MD: 4.2 kg/15mm CD: 3.1 kg/15mm	MD: 8.7 kg/25mm CD: 5.7 kg/25mm
Color	Black	Brown
Smoothness	Good	Good
Elongation	200±25%	
Die Cutting	Good	Good

Country of Origin: Taiwan