

Features

- Input TTL Level
- Output RS485
Protocoll (2 wires)
- Baudrate up to 9600
Baud
- Modbus
Communication RTU
Slave
- Red LED Indicators
for TX & RX Green
LED power indicator
- DIN rail mounting
- Weight of 80g

RS PRO PLCs - Programmable Logic Controllers

RS Stock No.: 917-6383, 917-6392



RS PRO Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

An RS485 communication module enabling communication between devices using the RS485 standard. The RS485 communications module provides Modbus communication and can be used to connect multiple devices making it ideal for use in automation applications in both commercial and industrial environments

General Specifications

RS Stock No	917-6383	917-6392
Supply Voltage	110-240 VAC	12-24 VDC
Input	TTL Level	
Output	RS 485 Protocol (Two wires, D +, D -)	
Number of Nodes	32 Standard unit loads	
Isolation Voltage	2000 Vrms	
Baud Rate	300, 600, 1200, 2400, 4800, 9600	
Operating Temperature	-10°C to + 55°C	
Storage Temperature	-20°C to + 70°C	
Modbus Communication	Yes (RTU)(Slave)	
LED Indications	Res LED's for Tx & Rx. Green LED for Power indication	
Ordering Information RS Stock No 917-6383 917-6392	110-240 VAC RS485Communication Module 12-24 VDC RS485Communication Module	

Approvals

Standards Met	CE,UL,RoHS
---------------	------------