E8431_I_WE_G2

Full-flat Intermediate switch, ZENcole, 16AX, 1 gang, white





Main	
Range	ZENcelo
Product or component type	Switch
Load type	Inductive Incandescent lamp Fluorescent lamp
Colour tint	White

White

Complementary

Device mounting	Flush Surface	
Switch function	1-way	
Rated current	16 AX at 250 V AC 50/60 Hz	
Number of gangs	1 gang	
Material	Polycarbonate + GF 20 %: grid plate Polycarbonate: base Polycarbonate: cover Polycarbonate: surround	
Connections - terminals	Pillar terminals	
Embedding depth	23.9 mm	
Width	87 mm	
Height	87 mm	
Depth	32.1 mm	

Cover frame colour tint

Environment

Ambient air temperature for operation	-535 °C
Relative humidity	095 %
Environmental characteristic	No UV resistant
Operating altitude	2000 m
Standards	MS IEC 60669-1 IEC 60669-1 GB 16915.1 SS 227-1 BS EN 60669-1

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	3.5 cm	
Package 1 Width	8.7 cm	
Package 1 Length	8.7 cm	
Package 1 Weight	124.47 g	
Unit Type of Package 2	BB1	
Number of Units in Package 2	8	

Package 2 Height	9.5 cm	
Package 2 Width	15 cm	
Package 2 Length	19 cm	
Package 2 Weight	995.76 g	
Unit Type of Package 3	CAR	
Number of Units in Package 3	80	
Package 3 Height	21 cm	
Package 3 Width	32.5 cm	
Package 3 Length	50 cm	
Package 3 Weight	9957.6 g	

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations