



ENGLISH

Datasheet

# RS Pro PVC Insulating Tape

RS Stock No: 134-7323



## Product Description

A lead free PVC Insulation tape coated with cross- linked solvent based rubber resin adhesive.

## Features

- Flame retardant
- Self-extinguishing
- Easy tear
- Easy unwind
- Flexible
- Conformable to awkward shapes
- Water resistant
- Good abrasion resistance
- UV resistant
- Non-corrosive adhesive

## NOTE

Except where indicated otherwise, the figures stated are average values and should not be regarded as MAXIMUM or MINIMUM values for specification purposes. The Company reserves the right to improve products and any change in specification will result in a re-issue of the relevant 'Technical Data Sheet'. Customers should satisfy themselves that the tape is suitable for their requirements whether after such modifications or otherwise. Please check that you have the latest issue of the 'Technical Data Sheet'. All slitting and length tolerances are to British Standards. Before use the customer is advised to consult the Health & Safety Data Sheet produced by the company for this product, which is available on request.

## STORAGE

Tapes stored below the minimum recommended temperature will require warming up to that level before use. Up to 24 hours may be required for this to take place.

## Technical Details

### Typical Values

|                         |                       |
|-------------------------|-----------------------|
| Thickness               | 0.13mm                |
| Breaking Load           | 26 N/cm               |
| Elongation              | 180%                  |
| Adhesion                |                       |
| Steel                   | 2.4 N/cm              |
| Self                    | 2.1 N/cm              |
| Water Extract           | pH 6.8                |
| Conductivity Max.       | 2 Ms/m                |
| Electrical Properties:  |                       |
| Breakdown Voltage       | 80 kV/mm              |
| 1 min Proof Test        | 6.0 kV                |
| Insulation Resist       | 10 <sub>11</sub> ohms |
| Copper Corrosion        | No Staining           |
| RoHS Compliant          | Yes                   |
| Service Temperature     | -5°C to +70°C         |
| Application Temperature | 0°C to +40°C          |
| Storage Temperature     | +12°C to +25°C        |