E3032RJ_WW 2 Gang RJ11 4 Pin Telephone Outlet, White





Main Product or component type Telephone socket type RJ11 (4 contacts) - category 3 Colour tint White

Complementary

Wiring device mounting	Flush	
	Surface	
Socket number	2	
Rated current	1.5 A at 125 Vrms AC	
Number of gangs	2 gangs	
Material	PBT 15 % FG: insert	
	PC: housing	
	Polycarbonate: plastic part	
Contacts material	Contact: phosphor bronze	
	IDC contact: phosphor bronze with tin plating	
Contact resistance	1000000 μOhm	
Insulation resistance	>= 1000 MOhm	
AWG gauge	AWG 26AWG 24 (2 twisted pair cables)	
Width	87 mm	
Height	87 mm	
Depth	36 mm	

Environment

Dielectric strength	750 V for 60 s at 60 Hz
Ambient air temperature for operation	040 °C
Relative humidity	095 %
Environmental characteristic	Indoor use
Standards	YD/T 577-92

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	3.6 cm	
Package 1 Width	8.7 cm	
Package 1 Length	8.7 cm	
Package 1 Weight	92 g	
Unit Type of Package 2	BB1	
Number of Units in Package 2	8	
Package 2 Height	9.5 cm	
Package 2 Width	15 cm	

Package 2 Length	19 cm	
Package 2 Weight	750 g	
Unit Type of Package 3	CAR	
Number of Units in Package 3	80	
Package 3 Height	21 cm	
Package 3 Width	31 cm	
Package 3 Length	50 cm	
Package 3 Weight	8500 g	

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	[™] REACh Declaration	
EU RoHS Directive	Compliant with Exemptions	
Mercury free	Yes	
China RoHS Regulation	China RoHS Declaration	
RoHS exemption information	€Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	No need of specific recycling operations	

Contractual warranty

Warranty	18 months
----------	-----------