

Composite and S-Video to HDMI Converter with Audio

Product ID: VID2HDCON



The VID2HDCON Composite and S-Video to HDMI® Video Converter (with Audio) lets you connect an S-Video or Composite device, along with supporting 3.5mm audio, to your HDMI monitor or television.

Equipped with convenient selector switches for easy configuration, the S-Video/Composite to HDMI converter is able to function with both NTSC and PAL systems, and offers support for output resolutions up to 1600x1200 (PC) or 1080p (TV) to seamlessly integrate with almost any display.

The converter features an integrated 3.5mm audio connection that enables sending the output through a single HDMI cable to your destination display, avoiding the hassle of running a separate audio cable.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

Certifications, Reports and Compatibility



Applications

- Convert VCRs, DVD players, camcorders, video game consoles and other home theater devices to work on HDMI displays

Features

- Functions with NTSC and PAL systems
- PC/TV resolution selector switch for compatibility with many different displays
- 50/60 Hz frame rate conversion
- On Screen Display
- Plug and play installation - no software/drivers required
- Advance 3D motion adaptive de-interlace
- 3D (frame based) motion adaptive YNR/CNR noise reduction

Hardware	Warranty	2 Years
	Active or Passive Adapter	Active
	Audio	Yes
	AV Input	3.5 mm Stereo Audio
		Composite
		S-Video
	AV Output	HDMI
	Industry Standards	NTSC 3.58 and PAL
Performance	Supported Resolutions	PC - 1600x1200, 1280x1024, 1024x768 TV - 1080p, 720p, 576p, 480p
Connector(s)	Connector Type(s)	1 - 3.5 mm Mini-Jack (3 Position) Female Input 1 - Composite Video (1 x RCA) Female Input 1 - HDMI (19 pin) Female Output 1 - S-Video (4 pin, Mini-DIN) Female Input
Indicators	LED Indicators	1 - Red - S-Video, Yellow - Composite Video
Power	Center Tip Polarity	Positive
	Input Current	0.3A
	Input Voltage	100 - 240 AC
	Output Current	1.2A
	Output Voltage	5 DC
	Plug Type	M
	Power Consumption (In Watts)	2.5
	Power Source	AC Adapter Included
Environmental	Humidity	20~90% RH
	Operating Temperature	0°C to 40°C (32°F to 104°F)
	Storage Temperature	-20°C to 60°C (-4°F to 140°F)
Physical Characteristics	Color	Black
	Enclosure Type	Plastic
	Product Height	3.4 cm [1.3 in]
	Product Length	16.4 cm [6.5 in]
	Product Width	16.3 cm [6.4 in]

	Weight of Product	79 g [2.8 oz]
Packaging Information	Package Height	56 mm [2.2 in]
	Package Length	12.4 cm [4.9 in]
	Package Width	15.5 cm [6.1 in]
	Shipping (Package) Weight	310 g [10.9 oz]
What's in the Box	Included in Package	1 - Composite/S-Video to HDMI Converter
		1 - Universal Power Adapter (NA/JP, EU, UK, ANZ)
		1 - Instruction Manual

Product appearance and specifications are subject to change without notice.