




Datasheet

RS PART NUMBER:	8850850
Product Discription:	Cable ZYRAD 500 2.5MM SQ
Specification No.:	UL3289 14AWG
Customer's Name:	

Description					Construction					
Rated Voltage:		600V			Conductor		Stranded Tinned Copper			
Rated Temperature:		150°C			Size(AWG)		14			
Reference Standard:		UL758,UL1581			Construction(±0.008mm)		50/0.25			
Cross Section					Stranded Dia.(mm)Ref.		2.07			
					Insulation Material		XL-PE			
					Insulation Color		Black			
					Ave Thickness(mm)		0.8			
					Insulation Dia.(±0.15mm)		3.67			
Marking					Remark:					
E148000RJ AWM STYLE 3289 14AWG 150°C 600V VW-1 --- cRJ AWM I A 150°C 600V FT1 -F- - LF- PC10 LTK										
Applications					Characteristics					Customer Approve
For use as Motor Leads or Internal Wiring of Appliances.					Test Item		Standard Value			Seal & Stamp Signature: Date:
					Test Material		XL-PE(ROHS)			
					Max.DC Resistance(20°C Ω/km)		8.99(MAX)			
					Vol. Tesr(AC.V.60S) (V)		2000			
Flammability Test		VW-1								
Revisions										
Version	Description	Drawn by	Approved by	Date						
0	New document issue	Lisa	Jason	07/07/2015						