# Product data sheet Characteristics

# A9N26948

# MX Shunt Trip MX plus 1 OF 24Vac dc





#### Main

Acti9
Shunt trip release with OC contact
MX + OF
1 C/O
1224 V AC 50/60 Hz 1224 V DC
2

#### Complementary

Range compatibility	Acti 9 (Acti9 iDPN)
	Acti 9 (Acti9 C120)
	Acti 9 (Acti9 C40)
	Acti 9 (Acti9 C60H-DC)
	Acti 9 (Acti9 C60NA-DC)
	Acti 9 (Acti9 C60PV-DC)
	Acti 9 (Acti9 DPN Vigi)
	Acti 9 (Acti9 DT40)
	Acti 9 (Acti 9 DT60)
	Acti 9 (Acti9 ID C40)
	Acti 9 (Acti9 IDc)
	Acti 9 (Acti9 ITG40)
	Acti 9 (Acti9 ID) Acti 9 (Acti9 DPN)
Local signalling	Action indicator
Mounting mode	Fixed
Mounting support	35 mm symmetrical DIN rail
Comb busbar and distribution block compatibility	Top: YES
Height	82.5 mm
Width	18 mm
Depth	73.5 mm
Net weight	65 g
Colour	White
Connections - terminals	Clamp terminal - 1 cable(s) 2.5 mm <sup>2</sup> - flexible
Wire stripping length	9 mm
Tightening torque	1 N.m
Compatibility code	MX + OF

#### Environment

Standards	EN/IEC 60947-5-1	
Product certifications	ASTA LCIE KEMA ASEFA	
Tropicalisation	2 conforming to EN/IEC 60947-5-1	
Relative humidity	95 % at 55 °C	
Ambient air temperature for operation	-2550 °C	
Ambient air temperature for storage	-4085 °C	

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8 cm
Package 1 Width	3 cm
Package 1 Length	9.3 cm
Package 1 Weight	74 g
Unit Type of Package 2	BB1
Number of Units in Package 2	8
Package 2 Height	8.7 cm
Package 2 Width	10 cm
Package 2 Length	26.5 cm
Package 2 Weight	652 g
Unit Type of Package 3	S03
Number of Units in Package 3	72
Package 3 Height	30 cm
Package 3 Width	30 cm
Package 3 Length	40 cm
Package 3 Weight	6.363 kg

## Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EPEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	☐ China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	☑ End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

#### Contractual warranty

Warranty	18 months