

**Repair Stick Wood****! SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

**Name of product** Repair Stick Wood  
Code-Nr. 105320

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Recommended intended purpose(s)**

2-Component Epoxy Resins

**1.3. Details of the supplier of the safety data sheet****Distributor**

WEICON GmbH & Co. KG  
Königsberger Str. 255, DE-48157 Münster  
Phone : +49(0)251 / 9322 - 0, Fax : +49(0)251 / 9322 - 244  
E-Mail : msds@weicon.de  
Internet : www.weicon.de

**Advice**

Produktsicherheit / Product-Safety-Department  
Phone : +49(0)251 / 9322 - 0  
Fax : +49(0)251 / 9322 - 244  
E-mail (competent person):  
msds@weicon.de

**1.4. Emergency telephone number**

EMERGENCY CONTACT - UK, UAE, South Africa (24h): Tel:  
++44 1865 407333 (English)  
TRANSPORT EMERGENCY CONTACT - UK, UAE, South  
Africa (24h): Tel: ++44 1865 407333 (English)

**Manufacturer**

WEICON GmbH & Co. KG  
Königsberger Str. 255, DE-48157 Münster

**1.4. Emergency telephone number**

GIFTNOTRUF/TRANSPORTNOTRUF - Deutschland (24h):  
Tel: ++49 69 222 25285 (Deutsch, Englisch)

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]**

Hazard classes and Hazard categories	Hazard Statements	Classification procedure
--------------------------------------	-------------------	--------------------------

Skin Irrit. 2	H315	
Eye Irrit. 2	H319	
Skin Sens. 1	H317	
Aquatic Chronic 3	H412	

**Hazard Statements**

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H412	Harmful to aquatic life with long lasting effects.

**2.2. Label elements**

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]



GHS07

**Signal word**

Warning

**Hazard Statements**

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H412	Harmful to aquatic life with long lasting effects.

**Precautionary Statements**

P102	Keep out of reach of children.
P261	Avoid breathing vapours/spray.
P264	Wash hands thoroughly after handling.
P272	Contaminated work clothing should not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/eye protection.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P362	Take off contaminated clothing.
P363	Wash contaminated clothing before reuse.
P501	Dispose of contents/container to hazardous or special waste collection point.

**! Hazardous ingredients for labeling**

2,4,6-Tri-(dimethylaminomethyl)phenol, 3-[3-(3-hydroxypropoxy)-2,2-bis[(3-hydroxypropoxy)methyl]propoxy]propan-1-ol; 3-sulfanylpropane-1,2-diol, reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)

**Special rules for supplemental label elements for certain mixtures**

Contains epoxy constituents. May produce an allergic reaction.

**2.3. Other hazards****Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**! SECTION 3: Composition/ information on ingredients****3.1. Substances**

not applicable

**3.2. Mixtures****Description**

2-component epoxy sticks



Safety Data Sheet according to Regulation (EC)  
No. 1907/2006 (REACH)

Printed 05.08.2019  
revision 23.11.2018 (GB) Version 8.6

**Repair Stick Wood**

**! Hazardous ingredients**

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
90-72-2	202-013-9	2,4,6-tris(dimethylaminomethyl)phenol	1 - 5	Acute Tox. 4, H302 / Eye Irrit. 2, H319 / Skin Irrit. 2, H315
25068-38-6	500-033-5	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	10 < 25	Eye Irrit. 2, H319 / Skin Irrit. 2, H315 / Skin Sens. 1, H317 / Aquatic Chronic 2, H411
72244-98-5	615-735-8	3-[3-(3-hydroxypropoxy)-2,2-bis[(3-hydroxypropoxy)methyl]propoxy]propan-1-ol; 3-sulfanylpropane-1,2-diol	10 - 20	Skin Sens. 1B, H317 / Aquatic Chronic 3, H412

**REACH**

CAS No	Name	REACH registration number
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	01-2119560597-27
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	01-2119456619-26
72244-98-5	3-[3-(3-hydroxypropoxy)-2,2-bis[(3-hydroxypropoxy)methyl]propoxy]propan-1-ol; 3-sulfanylpropane-1,2-diol	01-2120118957-46

**! SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**General information**

Remove contaminated soaked clothing immediately.

**In case of inhalation**

Ensure of fresh air.

In the event of symptoms refer for medical treatment.

**! In case of skin contact**

In case of contact with skin wash off with soap and water.

Consult a doctor if skin irritation persists.

**In case of eye contact**

After eye contact, rinse opened eye for 15 minutes under running water. Transfer to hospital for specialist examination.

**In case of ingestion**

Do not induce vomiting.

Call for a doctor immediately.

**4.2. Most important symptoms and effects, both acute and delayed**

**! Physician's information / possible symptoms**

skin irritation

**! Physician's information / possible dangers**

allergic reactions

**4.3. Indication of any immediate medical attention and special treatment needed**

No information available.

**! SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

**Suitable extinguishing media**

Alcohol-resistant foam

Dry fire-extinguishing substance

Carbon dioxide

Water spray jet



**Repair Stick Wood**

---

**! Unsuitable extinguishing media**

Full water jet

**5.2. Special hazards arising from the substance or mixture**

In case of fire formation of dangerous gases possible.

Nitrogen oxides (NO<sub>x</sub>)

Carbon monoxide (CO)

Carbon dioxide (CO<sub>2</sub>)

**5.3. Advice for firefighters**

**! Special protective equipment for fire-fighters**

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

Do not inhale explosion and/or combustion gases.

**! Additional information**

Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

---

**! SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

**! For non-emergency personnel**

Ensure adequate ventilation.

Remove persons to safety.

Use personal protective clothing.

Use breathing apparatus if exposed to vapours/dust/aerosol.

**6.2. Environmental precautions**

Do not discharge into surface waters/groundwater.

Do not discharge into the drains/surface waters/groundwater.

**6.3. Methods and material for containment and cleaning up**

After taking up the material dispose according to regulation.

Take up mechanically.

**6.4. Reference to other sections**

Safe handling: see section 7

Disposal: see section 13

Personal protection equipment: see section 8

---

**! SECTION 7: Handling and storage**

**7.1. Precautions for safe handling**

**! Advice on safe handling**

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

**! General protective measures**

Do not inhale vapours.

Avoid contact with eyes and skin

**! Hygiene measures**

At work do not eat, drink, smoke or take drugs.

Remove soiled or soaked clothing immediately.

Work in rooms with good ventilation.

Wash hands before breaks and after work.

**Advice on protection against fire and explosion**

Pay attention to general rules of internal fire prevention.

---

**Repair Stick Wood****7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep in closed original container.

**! Advice on storage compatibility**

Do not store together with animal feedstuffs.

Do not store together with food.

Do not store together with acids.

Do not store together with oxidizing agents.

**! Further information on storage conditions**

Protect from heat and direct solar radiation.

Store container at cool and aired place.

Store in a dry place.

**7.3. Specific end use(s)****Recommendation(s) for intended use**

See section 1.2

**! SECTION 8: Exposure controls/personal protection****8.1. Control parameters****! Ingredients with occupational exposure limits to be monitored**

CAS No	Name	Code	[mg/m <sup>3</sup> ]	[ppm]	Remark
65997-15-1	Portland cement: total inhalable dust	8 hours	10		EH40/2005
14807-96-6	Talc respirable dust	8 hours	1		EH40/2005
14807-96-6	Talk astbestfaserfrei (CH)	MAK, 8 hours	2		Lungenfib, Lunge, Methode: OSHA

**DNEL-/PNEC-values****DNEL worker**

CAS No	Substance name	Value	Code	Remark
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	8,33 mg/kg bw/day	DNEL long-term dermal (systemic)	
		12,25 mg/m <sup>3</sup>	DNEL long-term inhalative (systemic)	
		8,33 mg/kg bw/day	DNEL long-term dermal (local)	
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	0,31 mg/m <sup>3</sup>	DNEL long-term inhalative (systemic)	

**PNEC**

CAS No	Substance name	Value	Code	Remark
25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)	0,996 mg/kg	PNEC sediment, freshwater	
		11 mg/kg	PNEC Secondary Poisoning	
		0,018 mg/l	PNEC aquatic, intermittent release	
		0,0006 mg/l	PNEC aquatic, marine water	
		10 mg/l	PNEC sewage treatment plant (STP)	
		0,006 mg/l	PNEC aquatic, freshwater	
		0,0996 mg/kg	PNEC sediment, marine water	



# Safety Data Sheet according to Regulation (EC)

No. 1907/2006 (REACH)

Printed 05.08.2019

revision 23.11.2018 (GB) Version 8.6

## Repair Stick Wood

### DNEL-/PNEC-values (continued)

CAS No	Substance name	Value	Code	Remark
90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	0,0084 mg/l	PNEC aquatic, marine water	
		0,084 mg/l	PNEC aquatic, freshwater	
		0,2 mg/l	PNEC sewage treatment plant (STP)	

### ! Additional advice

The statutory local and national regulations have to be observed.

### 8.2. Exposure controls

#### ! Respiratory protection

Not required

#### Hand protection

In the cases of special applications, it is recommended to check the chemical resistance with the manufacturer of the gloves.

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]: Nitrile rubber; 0,4mm; 480min;60min.

Chemical protective gloves must be chosen carefully in view of their design and depending on the dependence on the concentration and amounts of dangerous goods used in the specific working tasks.

#### Eye protection

tightly fitting goggles

#### Other protection measures

protective clothing

#### Appropriate engineering controls

Sufficient ventilation and exhaustion.

## ! SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### Appearance

pasty

#### Colour

beige

#### Odour

hardly noticeable

#### Odour threshold

not determined

### Important health, safety and environmental information

	Value	Temperature	at	Method	Remark
<b>pH value</b>	not applicable				
<b>boiling point</b>	> 35 °C		ca. 101 kPa		
<b>melting point</b>	not applicable				
<b>Flash point</b>	> 100 °C				
<b>Vapourisation rate</b>	not applicable				
<b>Flammable (solid)</b>	not determined				
<b>Flammability (gas)</b>	not applicable				

**Repair Stick Wood**

	Value	Temperature	at	Method	Remark
<b>Ignition temperature</b>	> 200 °C				estimate
<b>Self ignition temperature</b>					The product is not self-igniting.
<b>Lower explosion limit</b>	not determined				
<b>Upper explosion limit</b>	not determined				
<b>Vapour pressure</b>	< 500 Pa	20 °C			
<b>Relative density</b>	ca. 0,9 g/cm <sup>3</sup>				
<b>Vapour density</b>	not applicable				
<b>Solubility in water</b>					insoluble
<b>Solubility/other</b>	not determined				
<b>Partition coefficient n-octanol/water (log P O/W)</b>	not determined				
<b>Decomposition temperature</b>	not determined				
<b>Viscosity dynamic</b>	not applicable				
<b>Viscosity kinematic</b>	not applicable				
<b>Oxidising properties</b>	No information available.				
<b>Explosive properties</b>	not applicable				
<b>9.2. Other information</b>	No information available.				

**! SECTION 10: Stability and reactivity****10.1. Reactivity**

No information available.

**10.2. Chemical stability**

The product is chemically stable under recommended conditions of storage, use and temperature.

**10.3. Possibility of hazardous reactions**

Reactions with acids and strong oxidising agents.

Reactions with amines.

**10.4. Conditions to avoid**

Keep away from heat.

**10.5. Incompatible materials****Substances to avoid**

Amines

Acid

Oxidising agent, strong

**Repair Stick Wood****10.6. Hazardous decomposition products**

Carbon monoxide and carbon dioxide.

Nitrous oxides (NOx)

Toxic gases/vapours

**Thermal decomposition**

Remark No decomposition if used as directed.

**! SECTION 11: Toxicological information****11.1. Information on toxicological effects****Acute toxicity/Irritation/Sensitization**

	Value/Validation	Species	Method	Remark
<b>LD50 acute oral</b>	29585 mg/kg			ATE
<b>LD50 acute dermal</b>	1 mg/kg	rat		CAS: 90-72-2
<b>Skin irritation</b>	irritant			
<b>Eye irritation</b>	irritant			
<b>Skin sensitization</b>	sensitizing			

**Subacute Toxicity - Carcinogenicity**

	Value	Species	Method	Validation
<b>Chronic Toxicity</b>				-
<b>Mutagenicity</b>				No experimental information on genotoxicity in vitro available.
<b>Reproduction-Toxicity</b>				No indications of toxic effects were observed in reproduction studies in animals.
<b>Carcinogenicity</b>				No indications of carcinogenic effects are available from long-term trials.

**! Experiences made from practice**

Often and long skin contact may cause degreasing and desiccation of the skin which may cause skin irritation.

Sensitization through skin contact possible.

Irritates mucous membranes.

Irritates eyes and skin.

**! Additional information**

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

The product has not been tested. The information is derived from the properties of the individual components.



**! SECTION 12: Ecological information****12.1. Toxicity****Ecotoxicological effects**

	Value	Species	Method	Validation
<b>Fish</b>	LC50 2 mg/l (96 h)	Oncorhynchus mykiss		CAS: 25068-38-6
<b>Daphnia</b>	NOEC 0,3 mg/l (21 d)	Daphnia magna		CAS: 25068-38-6
<b>Algae</b>	EC50 220 mg/l (96 h)	Scenedesmus subspicatus		CAS: 25068-38-6

**12.2. Persistence and degradability**

	Elimination rate	Method of analysis	Method	Validation
<b>Biological degradability</b>	12 % (28 d) CAS: 25068-38-6			not degradable

**12.3. Bioaccumulative potential**

The product has not been tested. Because of the product's consistency and low solubility in water bioavailability is not likely.

**12.4. Mobility in soil**

no

**12.5. Results of PBT and vPvB assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6. Other adverse effects****! General regulation**

Harmful to aquatic life with long lasting effects.

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into aquatic environment, drains or sewage treatment plants.

The ecotoxic effect of the product has not been tested. The information on this is given on the basis of details in the literature.

**! SECTION 13: Disposal considerations****13.1. Waste treatment methods****! Recommendations for the product**

Remove in accordance with local official regulations.

**Recommendations for packaging**

Untampered packaging may be treated as household waste.

Packaging that cannot be cleaned should be disposed of like the product.

**General information**

Assignment to a waste code number / waste identification according to the EWC is to be carried out on a sector or process-specific basis.

**SECTION 14: Transport information**

	ADR/RID	IMDG	IATA-DGR
<b>14.1. UN number</b>	-	-	-
<b>14.2. UN proper shipping name</b>	-	-	-

**Repair Stick Wood**

---

	ADR/RID	IMDG	IATA-DGR
<b>14.3. Transport hazard class(es)</b>	-	-	-

<b>14.4. Packing group</b>	-	-	-
----------------------------	---	---	---

<b>14.5. Environmental hazards</b>	-	-	-
------------------------------------	---	---	---

**14.6. Special precautions for user**

No information available.

**14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

not applicable

**Transport/further information**

No dangerous goods as defined by the transport regulations - ADR/RID, IMDG, ICAO/IATA-DGR.

---

**! SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****VOC standard****VOC content** 0 %**15.2. Chemical Safety Assessment**

Chemical safety assessments for substances in this mixture were not carried out.

---

**! SECTION 16: Other information****! Recommended uses and restrictions**

National and local regulations concerning chemicals shall be observed.

For industrial use only.

**Further information**

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

Indication of changes: "!" = Data changed compared with the previous version. Previous version: 8.5

H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.