

USB-C Adapter

multicomp **PRO**

RoHS
Compliant



Features

- Fits standard XLR Ø24mm cutout.
- No soldering or punch termination. Use standard cable for each connector style.
- Front or rear mounted.
- Low rear profile
- 90° or right angle rear cable entry.


Specifications

Max. Rated Current	: 3A
Max. Working Voltage	: 30V
Dielectric Withstanding Voltage	: 100V AC (min) 1 minute
Contact Resistance	: 40mΩ maximum
Insulation Resistance	: 100 MΩ minimum @100V DC
Insertion Life	: 10,000 Cycles
Power Delivery (PD) Compatible	: Yes

Materials

Frame	: PA66, UL94 V-2
RAFT Insert	: ABS, UL94 HB
USBC Insulator	: LCP, UL94 V-0

Diagram



Receptacle to Plug connection:

A1 to A1, A2 to A2, A3 to A3 etc..
B1 to B1, B2 to B2, B3 to B3 etc..

Dimensions : Millimetres

Part Number Table

Description	Part Number
USB-C Adapter, F-M, R/A, CSK Holes	MP-CP30256

Note: Functionality is affected by cable quality, length and cable wiring configuration.

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro
Farnell.com/multicomp-pro
sg.element14.com/b/multicomp-pro

multicomp **PRO**