

Datasheet

## RS Pro 30W/m Trace Heating Cable Constant Wattage, 240 V, 20m

RS Stock No: **665-7514**



### Product Details

RS Pro 30 W/m trace heating cable is designed to be cut from reel lengths and site terminated to suit pipe work. The constant wattage tape consists of number of short heating zones, each connected across a pair of continuous bus-wire conductors. Each complete heating zone will give its full rated design output with circuit voltage applied to the bus-wire conductors. This cable measuring 20 m, has a voltage rating of 240 V. The heating cable meets EX (certificate NO Sira 03ATEX3376U) and ATEX standards.

### Features and Benefits

- Parallel circuit - constant watt for hazardous areas
- Constant wattage tape consists of number of short heating zones
- Meets EX (certificate NO Sira 03ATEX3376U) and ATEX standards



ENGLISH

### Specifications:

Cable Type	Constant Wattage, Trace Heating
Hazardous Area Certification	ATEX
Length	20 m
Maximum Operating Temperature	+200°C
Minimum Operating Temperature	-60°C
Operating Temperature Range	-60 to +200°C
Output per Metre	30 W
Self Regulating	No
Sheath Material	Silicone Rubber
Standards Met	BS EN 60079-0:2009, BS EN 60079-30-1:2007
Voltage Rating	240 V