

## Datasheet

**RS Pro P40 Series Wire-Wound Potentiometer with a 6.35 mm Dia. Shaft, 10k $\Omega$ ,  $\pm$ 10%, 3W,  $\pm$ 150ppm/ $^{\circ}$ C, Panel Mount**  
RS Stock No: **842-7090**



## Product Details

RS Pro wire-wound potentiometer offers resistance up to 10 k $\Omega$  with a temperature coefficient of  $\pm$ 150ppm/ $^{\circ}$ C. This 3 W rated potentiometer includes a 6.35 mm diameter shaft and provides 285 $^{\circ}$  rotation.

## Features and Benefits

- $\pm$ 10% standard resistance tolerance
- 285 $^{\circ}$  rotation (mechanical angle)
- Power rating of 3W

**Specifications:**

Element Material	Wire Wound
Linearity	±0.75%
Mounting Type	Panel Mount
Termination Style	Solder
Mechanical Rotation	285°
Shaft Length	25 mm
Diameter	40 mm
Dimensions	40 (dia.) x 41 mm
Length	41 mm
Maximum Operating Temperature	+105°C
Maximum Resistance	10 kΩ
Minimum Operating Temperature	-40°C
Mounting Hole Diameter	15 mm
Power Rating	3 W
Temperature Coefficient	±150 ppm/°C
Tolerance	±10%
Number of Turns	1
Shaft Diameter	6 mm
Dielectric Strength	500 V ac
Insulation Resistance	1000 MΩ