



## Overview

Lead time	Usually in Stock
-----------	------------------



## Main

Main Input Voltage	230 V
Main Output Voltage	230 V
Output connector type	Hard wire 3-wire (H N + E) 3
Number of rack unit	4U
Number of cables	1
Provided equipment	Installation guide Rack mounting brackets User manual

## Physical

Colour	Black
Height	17.8 cm
Width	43.2 cm
Depth	67.3 cm
Net weight	21.82 kg
Mounting location	Front
Mounting preference	Lower
Mounting mode	Rack-mounted

## Input

Network frequency	50/60 Hz
Number of input connectors	1 hard wire 3-wire (H N + E) 1 hard wire 4-wire (3P + E)
Max line current	100 A
Input current limits	100 A
Load capacity	20000 VA
Power factor	0...1

## Output

Max current draw	100 A
Protection type	Circuit breaker
Efficiency	99 %

## Conformance

Product certifications	CSA[RETURN]GOST
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

## Environmental

Ambient air temperature for operation	-20...45 °C
Relative humidity	0...95 %
Operating altitude	0...15000 ft
Ambient air temperature for storage	-40...65 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.00...15240.00 m

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	30.5 cm
Package 1 Width	61 cm
Package 1 Length	99.1 cm
Package 1 Weight	31.753 kg
Unit Type of Package 2	PAL
Number of Units in Package 2	8
Package 2 Height	129.5 cm
Package 2 Width	100 cm
Package 2 Length	120 cm
Package 2 Weight	266.08 kg

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

Warranty	2 years (parts only)
----------	----------------------