




ENGLISH

Stainless Steel Adjustable Levelling Feet

The RS Pro Height Adjustable mounts are used for levelling and support, these are used in many applications including food processing units, packing systems and conveyor systems.

The base rubber is made of oil resistant 80 ShA Vulcanized NBR along with the Stainless Steel thread and base plate these are often used in food safe and cleanroom applications.

These mounts have a 10 degree articulation capabilities.



Item Code	Description	Α	В	D	F	G	Н	Static Load
		(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(kg)
1854513	Adjustable Height	29	50	50	M10	19	79	400
	Mount 10 Degree							
	Articulation with							
	Stainless Steel 304							
1854515	Adjustable Height	29	100	50	M10	19	129	400
	Mount 10 Degree							
	Articulation with							
	Stainless Steel 304							
1854516	Adjustable Height	29	100	50	M12	19	129	400
	Mount 10 Degree							
	Articulation with							
	Stainless Steel 304							

1854517	Adjustable Height	29	150	50	M12	19	179	400
1004017		29	150	50	IVI12	19	1/9	400
	Mount 10 Degree							
	Articulation with							
	Stainless Steel 304							
4054500	A.P. stable Helali	20	400		B44.6	25	420	4000
1854520	Adjustable Height	38	100	80	M16	25	138	1000
	Mount 10 Degree							
	Articulation with							
	Stainless Steel 304							
1854521	Adjustable Height	38	150	80	M16	25	188	1000
1007021	Mount 10 Degree	33	150	55	14110	25	100	1000
	Articulation with							
	Stainless Steel 304							
	Glairiless Gleer 504							
1854522	Adjustable Height	42	100	100	M16	30	142	1500
	Mount 10 Degree							
	Articulation with							
	Stainless Steel 304							
1854523	Adjustable Height	42	150	100	M20	30	192	1500
	Mount 10 Degree							
	Articulation with							
	Stainless Steel 304							
1854524	Adjustable Height	42	200	100	M20	30	242	1500
	Mount 10 Degree							
	Articulation with							
	Stainless Steel 304							
1854525	Adjustable Height	42	200	100	M16	30	242	1500
	Mount 10 Degree							
	Articulation with							
	Stainless Steel 304							