## Product data sheet Characteristics

## LVSXS113

Modular enclosure, PrismaSeT XS, flush, 1 x 13 modules, 1 earth + 1 neutral + 1 phase terminal blocks, without door





Main	
Range	PrismaSeT
Product name	XS
Product or component type	Enclosure
Enclosure type	Distribution enclosure
Enclosure mounting	Flush

Complementary

Complementary	
Width	351 Mm total: 321 mm embedded:
Height	360 Mm total: 330 mm embedded:
Depth	109 Mm total: 66 mm embedded:
Internal depth	80 mm
Number of 18 mm modules per row	13
Number of horizontal rows	1
Total number of 18 mm modules	13
9 mm pitches	26
Electrical insulation class	Class II
Provided equipment	1 identification label 1 label protector 3 terminal block 1 blanking plate strip 1 door to be ordered separately 1 DIN rail 1 back plate
Type of front plate	Modular
Type of rail	Symmetrical DIN
Mounting plate description	Without mounting plate
Power dissipation in W	34 W
[In] rated current	63 A
[Ui] rated insulation voltage	400 V
Cable entry	Cable or tube Cut-out plates Removable plates
Number of terminal blocks	1 earth with 14 outgoers 1 neutral with 4 outgoers 1 phase with 4 outgoers
Distribution block outgoers	3 x 25 mm <sup>2</sup> + 11 x 4 mm <sup>2</sup> for earth 4 x 16 mm <sup>2</sup> for neutral 4 x 16 mm <sup>2</sup> for phase

Connections - terminals	Screw connection (earth), 3 x 625 mm <sup>2</sup>	
	Push-in (earth), 11 x 1.54 mm² (flexible)	
	Push-in (earth), 11 x 6 mm² (rigid or stranded)	
	Screw connection (neutral), 4 x 16 mm <sup>2</sup>	
	Screw connection (phase) , 4 x 16 mm <sup>2</sup>	
Enclosure material	Back part: technoplastic	
	Enclosure: technoplastic	
	Front plate: technoplastic	
Net weight	2.280 kg	
Colour	Enclosure: white (RAL 9003)	
	Front plate: white (RAL 9003)	
Market segment	Residential	
	Small buildings	

## Environment

Fire resistance	Back plate: 850 °C conforming to IEC 60695-2-11 Enclosure: 750 °C conforming to IEC 60695-2-11 Front plate: 750 °C conforming to IEC 60695-2-11
IP degree of protection	IP30 without door IP40 with door
IK degree of protection	IK08 without door IK09 with door
Overvoltage category	II
Ambient air temperature for operation	-2560 °C
Standards	IEC 60670-1 IEC 60670-24 IEC 61439-1 IEC 61439-3
Quality labels	IMQ

## Offer Sustainability

Onor Odolamability	
Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EV RoHS  Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₽¥Yes
Environmental Disclosure	Product Environmental Profile