

FEATURES

- High quality nylon tyre
- Swivel castors
- Non-slip rubber feet
- Vibration damping rubber feet

RS PRO Swivel Swivel Castor, 1500kg Load Capacity, 96mm Wheel Diameter

RS Stock No.: 611-4464



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.



Product Description

RS PRO castors are a range of multifunction levelling castors. These wheels are versatile and are an ideal choice for equipment that needs to be mobile, but when in place is completely firm and stationary. They can be used in numerous applications such as Vending machines, Medical appliances and Workstations. The plate is steel with a khaki powder coating whilst the bracket is aluminium die-casting, also featuring bi-level balls upon balls for full swivel.

General Specifications

Rotation	Swivel
Weight Class	Heavy Duty
Load Capacity	1500kg /1pcs
Load Capacity / 4pcs	3000kg
Tyre Material	Nylon
Hub Material	Nylon
Includes Brake	No
Features	Corrosion Resistant, Impact Resistant, Shock Absorbing
Applications	Vending machines, Medical appliances, Workstations, Measuring Instruments

Mechanical Specifications

Mounting Type	Plate
Wheel Diameter	90mm
Wheel / Tread Width	55mm
Overall Height	132mm
Number of Fixing Holes	4
Fixing Hole Size	13mm
Hub Bearing Type	Ball Bearing
Levelling Extent	15mm
Offset	69mm



Fixing Centres Specifications	
Fixing Centres	100mm x 100mm
Fixing Centres (Length)	100mm
Fixing Centres (Width)	100mm

Fixing Plate Specifications	
Fixing Plate Dimensions	70mm x 70mm
Fixing Plate Length	70mm
Fixing Plate Width	70mm

Operation Environment Specifications

Operating Temperature	-10°C to 90°C
-----------------------	---------------







Castor Wheels



Technical Data

Wheel Diameter	90 mm
Width of Tread	55 mm
Hardness of Tread	70 Shore D
Size of Plate	100 x 100 mm
Plate Hole Centers	70 x 70 mm
Plate Hole	13 mm
Leveling Extent	15 mm
Offset	69 mm
Overall Height	132 mm
Temperature	-10 ∼ +90 °C
Load Capacity / 1pcs	1,500 kg
Load Capacity / 4pcs	3,000 kg



