

RoHS
Compliant

Cable Construction

Conductor	: Class 5 electrolytic bare flexible copper conductor conforming to IEC 60228 standard Size : 2 × 2.5mm ² : Stranding 48 × 0.243
Insulation	: Special TI6 complies with EN 50363-7, halogen-free thermoplastic insulation with improved fire resistance. Hardness : (44 ± 1) Sh-D Diameter 3.6 ± 0.1 Radial thickness of insulation ≥ 0.8 Colours Red and Blue
Jacket	: TM7 halogen-free thermoplastic outer sheath with improved fire resistance Outer diameter 9.3 ± 0.2mm Thickness ≥ 1mm Colour Black
Marking	: Evolution XPC OFC 2 × 2.5mm CCA LSZH Speaker Cable 301-123WH

Electrical Characteristics 20°C

Electrical resistance	: ≤ 7.98 Ω/Km
Temperature range	: - 20°C ÷ 70°C (@ fixed installation)
Short-circuit Temperature	: 160°C
Test voltage	: 2500V AC
Fire spread	: IEC 60332-1-2 CPR class Cca-s1, d1, a1
Halogen-free	: EN 50525-1, EN 50267-2-2, EN 50267-2-1
Bending radius	: ≥ 7 × D (@ fixed installation)
Application	: Halogen-free thermoplastic jacketed and insulated speaker cables, intended for the interconnection of receivers or power amplifiers to speakers
Installation	: Suitable for fixed installation Suitable for indoor use

Part Number Table

Description	Part Number
LSZH Speaker Cable, 2 x 2.5mm, White, 100m	MP007926

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.