

Datasheet

Anti-Static Heat Seal ESD-Safe Bag

RS Stock number **2877773**



Description

- Shielding bags are designed to protect ESD sensitive components and assemblies from all harmful aspects of static electricity. Their Faraday cage design ensures ESD safety.
- Critical metal layer is sandwiched between static-dissipative layers to protect the static shield.
- Surface resistivity of the metal layer is less than 10^2 OHMS per square to shield against static charges.
- Static-dissipative polyethylene inner layer is amine-free, polycarbonate compatible and octanoic acid –free.

Specifications

- Closure Type
- Height
- Material Properties
- Quantity per Package
- Width
- Heat Seal
- 24in
- Anti-Static
- 100 Each
- 18in



Electrical Properties	Typical Values	Test Method
• Surface Resistance		
• Outer Surface	1 x 10 ⁴ to < 1 x 10 ¹¹ ohms	IEC 61340-2-3
• Inner Surface	1 x 10 ⁴ to < 1 x 10 ¹¹ ohms	IEC 61340-2-3
• Discharge Shielding	<20 n J	ANSI/ESD STM11.31
• Charge Generation	Teflon: 0.09 nC/sq. in. Quartz: 0.01 nC/sq. in.	Modified Incline Plane Modified Incline Plane
• Capacitance Probe (to dissipate 1 KV)	<30V	EIA 541
• Chemical Properties		
• Corrosion	No effect on aluminum, copper, silver, Sn-Pb coated foil, stainless steel, low carbon steel	
• Polycarbonate Capability	Yes	