



Plunger针轴):Heat-Tredted Beryllium Copper With Rhodiun Plated Over Nickel(铍铜镀铑)

Spring(弹簧):Stainless Steel(不锈钢)

Barrel(内管):Phosphor Bronze With Gold Plated(磷青铜镀金)

最小中心距 (Min. Center) :2.54mm[0.10]

最大行程 (Full Stroke) : 21# 23#  
 4.2mm 3.0mm  
 [0.1654] [0.1181]

行程全压弹力 (Full Stroke Spring Force) : ±20%  
 150g[5.29oz]

2/3行程弹力 (2/3 Storke Spring Force) : ±20%  
 115g[4.06oz]

额定电流 (Current Rating) :3A

接触电阻 (Contact Resistance) :30mΩ

建议钻孔尺寸 (Recommended Hole Size)

压克力 (Acrylic) :1.70mm[0.0669]

电木板 (Bakelite) :1.75mm[0.0689]

玻璃纤维板 (Fiber Reinforce Plastic) :1.75mm[0.0689]



变更记录 MODIFY RECORD	△3						
	△2						
	△1						
	序号 NO:	变更内容 MODIFY CONTENT			变更者 WRITER	审核 CHECKED	日期 DATE
品名 DESCRIPTION	探针				版本 VERSION	A	日期 DATE
机种 MODEL NO.	521611				制图 DRAWING	Caizhengfeng	
料号 PART NNO.		公差 TOLERANCE	±0.1	比例 SCALE	审核 CHECKED	Du mengke	
图号 DRAWING NO.	FCT020	第三角法 3RD.ANGLE		单位 UNIT	批准 APPROVED	MM	