



## Main

Range	ZENcolo
Product or component type	Switch
Load type	Fluorescent lamp Resistive Inductive Incandescent lamp
Colour tint	White
Cover frame colour tint	White

## Complementary

Device mounting	Flush Surface
Switch function	2-way
Rated current	20 A at 250 V AC 50/60 Hz 16 AX
Local signalling	Mechanical indicator (amber)
Number of gangs	3 gangs
Material	Polycarbonate + GF 20 %: grid plate Polycarbonate: base Polycarbonate: cover Polycarbonate: surround
Connections - terminals	Brass rod terminals
Width	87 mm
Height	87 mm
Depth	31 mm

## Environment

Ambient air temperature for operation	-5...35 °C
Relative humidity	0...95 %
Environmental characteristic	No UV resistant
Operating altitude	2000 m
Standards	MS IEC 60669-1 IEC 60669-1 GB 16915.1 SS 227-1 EN 60669-1

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	133.08 g
Package 1 Height	3.5 cm
Package 1 Width	8.7 cm
Package 1 Length	8.7 cm

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>