

Data sheet

BNC STRAIGHT BULKHEAD JACK CRIMP

RS stock No: 5463743

NO	DESCRIPTION	DATE
△	BACKGROUND FORMAT UPDATED	09.29.08
△	DEL CABLE RETENTION	06.17.10
△	DEL INTERFACE	08.04.11
△	DEL PROOF VOLTAGE / ADD VSWR WORKING VOLTAGE → VOLTAGE RATING	04.30.13

APPROVED _____ by _____ DATE: _____

DESCRIPTION	BNC STRAIGHT BULKHEAD JACK CRIMP	
DRAWN	TOLERANCE	品名 13-11 T.GIN 58U 日 DATE 版 REV.
Yoko	X ±0.2	ROHS COMPLIANT (500) 期 01.15.92 次 B-4
CHECK	.XX ±0.1	UNIT
Arc	.XXX ±0.05	mm(In)
APPROVAL	.XXX ±0.05	DWG.NO. 13-0106\times(13-011-00-01)</math>
認定	ANGLE ±5°	SCALE
Jenny	3:1	

1.0 ELECTRICAL

1.1 FREQUENCY RANGE: DC-4 GHz

1.2 NOMINAL IMPEDANCE: 50 OHMS

1.3 VOLTAGE RATING: 500 VOLTS MAX. △

1.4 VSWR: 1.5 MAX. @ 8 GHz △

2.0 MATERIALS

2.1 BODIES: BRASS PER JIS-C3604

2.2 CENTER CONTACT: BRASS PER JIS-C3604

2.3 INSULATION: TEFLON PER ASTM D1467 AND ASTM D1710

2.4 CRIMP FERRULE: BRASS PER JIS-C2700

3.0 FINISHES AND OTHERS

3.1 SEE BELOW TABLE FOR DETAILS.

4.0 MECHANICAL

4.1 FOR USE WITH RG58U OR SIMILAR STYLE CABLE

4.2 CABLE ATTACHMENT: OUTER: CRIMP, INNER: SOLDER/CRIMP

4.3 CRIMP SIZE REQUIRED: CONTACT: 1.8\times(071) HEX. CRIMP TOOL FERRULE: 5.5\times(216) HEX. CRIMP TOOL

5.0 ENVIRONMENTAL

5.1 OPERATING TEMPERATURE RANGE: -85° C TO +168° C

NO	DESCRIPTION	MATERIAL	Q'TY	FINISH
8	CENTER CONTACT	BRASS	1	GOLD
7	CRIMP FERRULE	BRASS	1	NICKEL
6	CHASSIS	BRASS	1	NICKEL 100μ" MIN.
5	GASKET	SILICONE	1	NONE
4	INSULATION	TEFLON	1	NONE
3	BODY	BRASS	1	NICKEL 100μ" MIN.
2	WASHER	STEEL	1	NICKEL
1	NUT	BRASS	1	NICKEL