Cable Assembly

multicomp PRO



RoHS Compliant

Specifications

Electrical

Current Rate : 2A

Environmental

Operating Temperature Range : -40°C to +85°C

Mechanical

 $\begin{array}{lll} \mbox{Spring Force} & : 25 \pm 20\% \mbox{ gf} \\ \mbox{Working Stroke} & : 1.2 \mbox{mm} \\ \mbox{Durability} & : 10,000 \mbox{ cycles} \end{array}$

Material

Plunger : Brass C3604, 3µ" gold Plating Barrel : Brass C3602, 3µ" gold Plating

Spring : SUS304

Housing : PA46 +30% GF, Black


Magnet : NdFeB, N52


Cable : PVC, Black, OD 3.5mm , Length 2m

AWG24×2C+AWG28×2C, 70P

USB : PVC

Diagram







General Tolerance

 $X. = \pm 0.3$ mm $.X = \pm 0.15$ mm $.XX = \pm 0.1$ mm

Pin Assignment					
USB	Mag Pin	Signal	Wire gauge	Colour	
1	Pin1	VCC	AWG24	Red	
2	Pin2	DATA-	AWG28	White	
1	Pin3	/	1	/	
3	Pin4	DATA+	AWG28	Green	
4	Pin5	GND	AWG24	Black	

Dimensions: Millimetres

Part N	lumbe	r Table
--------	-------	---------

Description	Part Number
USB Cable Assembly, 5 Pin, 100cm	MP011973

Important Notice: This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro sg.element14.com/b/multicomp-pro

