Eaton NON-2

Catalog Number: NON-2

Eaton Bussmann series NON fuse, Non current limiting, Light duty circuit locations, 2 A, Class H, Non-indicating, Ferrule end x ferrule end, 50 kAIC at 125 Vdc|50 kAIC at 250 Vac, Standard, 10, 250 V, 125 Vdc

General specifications



Eaton Bussmann series NON fuse

UPC

051712300025

Product Height

0.56 in

Product Weight

0.35 lb

Compliances

CE Marked

Catalog Number

NON-2

Product Length/Depth

2 in

Product Width

0.56 in

Warranty

Not Applicable



Electrical rating

Amperage Rating

2 A

Interrupt rating

50 kAIC at 250 Vac 50 kAIC at 125 Vdc

Voltage rating

250 Vac, 125 Vdc

Physical details

Packaging type

Standard

General information

Class

Class H

Connection

Ferrule end x ferrule end

Fuse indicator

Non-indicating

Quantity

10

Special features

Non current limiting

Resources

Catalogs

Bussmann series complete full line catalog no. 1007

Multimedia

Bussmann series Fuseology

Specifications and datasheets

Eaton Specification Sheet - NON-2

Technical data sheets

NON-2~BUSS ONE TIME FUSE

Technical service bulletins

Datasheet - FNQ-30



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2023 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia