Eaton FWH-30A14F

Catalog Number: FWH-30A14F

Eaton Bussmann series FWH high speed fuse, 1000 Vac, 800 Vdc, 30A, 200 kAIC Vac, 50 kAIC at 500 Vdc, Non Indicating, High speed fuse, Ferrule end X ferrule end

General specifications

Product Name

Catalog Number

Eaton Bussmann series high speed

FWH-30A14F

cylindrical fuse

UPC

051712370844

EAN

Product Length/Depth

5027590499620

55 mm

Product Height

Product Width

32 mm

73 mm

Product Weight

Warranty

20.4 g

Not Applicable

Compliances

Certifications

CE Marked

CSA Certified

RoHS Compliant

UL Recognized



Product specifications Fuse indicator Other Interrupt rating 50 kAIC Construction size 14 mm x 51 mm Clearing (I2T) 232 at 500 V Connection Ferrule end x ferrule end Material Ceramic Release characteristic Other **Amperage Rating** 30 A Frequency rating - max 62 Hz Utilization category aR (accompanied semiconductor protection) Watt losses 9 W Fuse type FWH-A14F Accessories CH14 Modular fuse holder FW14-PCB Type High speed fuse Fuse shape Cylindrical Breaking capacity 200 kA

Fuse size 14 x 51 mm

Resources

Catalogs

IEC high speed fuse links

Bussmann series complete full line catalog no. 1007

Compliance information

CE FWC-*A10F,FWH-*A14F,FWP-*A14F,FWP-*A14FI etc

UKCA FWC-*A10F,FWH-*A14F,FWP-*A14F,FWP-*A14FI etc

Technical data sheets

720008 FWH

Frequency rating - min

45 Hz

Class

Class aR

Pre arc (I2T)

58

Voltage rating

500 V

Application

Semiconductor, DC Common bus, DC drives, Power converters/rectifiers

Voltage type

AC/DC

Packaging type

Standard



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2023 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia