

## **FEATURES**

- Operating temperature range is from - 60 °C to + 300 °C
- RoHS and REACH
  compliant
- Silicon free

# RS PRO REDUCTION -COMPRESSION

RS Stock No.: 2312571



RS PROfessionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the

leading brands without paying a premium price.



#### **Product Description**

The RS PRO elbow female adaptor compression is made up of brass.

The working pressures and working temperatures depend on which type of tube is used, for this reason, the values must be determined in accordance with the tube's features.

Hereunder, we specify the values of the maximum pressure advised for the fittings at a temperature of 20° C connected with copper tube, which has a thickness of 1 mm.

Here the tube size is 6 and corresponding maximum pressure advised is 148.4 bar.

#### **General Specifications**

Fitting Type	Elbow
Angle	90°
Material	Brass
Fitting Direction	Elbow
Application	Compressed Air, Pneumatic Automation, Industrial water circuits, Inert Gases, Fluids, Steam Vacuum

#### **Mechanical Specifications**

Pipe Fitting Connection Type	Threaded		
Connection 1	M14 Metric Female		
Connection Gender 1	Female		
Thread Size 1	M14		
Thread Standard 1	Metric		
Connection 2	1/8 in BSPP Female		
Connection Gender 2	Female		
Thread Size 2	1/8 in		
Thread Standard 2	BSPP		
Length 1	24mm		
Length 2	18mm		
Wrench Size	9mm		



Operation Environment Specifications				
Comporatura	Min.	Max.		
mperature	- 60°C	+ 300°C		


Ар	prov	als

Approvals	RoHS and REACH compliant

### Similar Products

Parameters	2312588	2312589		
Brand	RS PRO	RS PRO		
Pipe Fitting Connection Type	Threaded	Threaded		
Connection 1	M14 Metric Female	M14 Metric Female		
Connection Gender 1	Female	Female		
Thread Size 1	M14	M14		
Thread Standard 1	Metric	Metric		
Connection 2	1/4 in BSPT Male	1/8 in BSPT Male		
Connection Gender 2	Male	Male		
Thread Size 2	1/4 in	1/8 in		
Thread Standard 2	BSPT	BSPT		
Length	29.5mm	28mm		
Wrench Size	14mm	11mm		





Tube	А	В	L1	L2	СН	Pack.
6	1/8	8.5	24	18	9	10