E8433_1_SA_G2

ZENcelo-16AX/20A 3 Gang 1 Way Full-Flat Switch with Ondicator - Silver Satin.





Main	
Range	ZENcelo
Product or component type	Switch
Load type	Resistive Fluorescent lamp Inductive Incandescent lamp
Colour tint	Silver satin
Cover frame colour tint	Silver satin

Complementary

Complementary		
Device mounting	Surface	
	Flush	
Switch function	1-way	
Rated current	20 A at 250 V AC 50/60 Hz	
Local signalling	Mechanical indicator (amber)	
Number of gangs	3 gangs	
Material	Polycarbonate + GF 20 %: grid plate	
	Polycarbonate: base	
	Polycarbonate: cover	
	Polycarbonate: surround	
Connections - terminals	Brass rod terminals	
Width	87 mm	
Height	87 mm	
Depth	31 mm	

Environment

Ambient air temperature for operation	-535 °C
Relative humidity	095 %
Environmental characteristic	No UV resistant
Operating altitude	2000 m
Standards	EN 60669-1 MS IEC 60669-1 GB 16915.1 IEC 60669-1 SS 227-1

Packing Units

PCE	
1	
3.5 cm	
8.7 cm	
8.7 cm	
134.49 g	
S04	
80	
30 cm	
	1 3.5 cm 8.7 cm 8.7 cm 134.49 g S04

Package 2 Width	40 cm
Package 2 Length	60 cm
Package 2 Weight	11.817 kg
Unit Type of Package 3	P12
Number of Units in Package 3	1600
Package 3 Height	125 cm
Package 3 Width	105 cm
Package 3 Length	80 cm
Package 3 Weight	237.928 kg

Offer Sustainability

Green Premium product
REACh Declaration
Yes
Compliant EEU RoHS Declaration
Yes
Yes
☑ China RoHS Declaration
€Yes
Product Environmental Profile