

TECHNICAL DATA

Fluke BP7235 NiMH Battery Pack



Key features

7.2V 3500 mA-hour rechargeable Ni-MH battery pack. This item replaces BP7217 Ni-Cd Battery Pack

Includes one battery pack.

Product overview: Fluke BP7235 NiMH Battery Pack

7.2 V 3500 mA-hour rechargeable Ni-MH battery pack. Provides typical 16-hour battery life when used in 700 or 740 Calibrator.

Specifications: Fluke BP7235 NiMH Battery Pack

General Specifications	
Material	Six 1.2 V DC Ni-MH cells in custom-molded ABS/PC-blend case
Application	7.1 x 2.2 x .9 in (150 x 56 x 22 mm)
Dimensions	7.1 x 2.2 x .9 in (150 x 56 x 22 mm)
Weight	11 oz / 310g
Warranty	One year

This item replaces BP7217 Ni-Cd Battery Pack.

Ordering information



Fluke BP7235

NiMH Battery Pack

Fluke. *Keeping your world up and running.®*

Fluke Corporation
PO Box 9090, Everett, WA 98206 U.S.A.

For more information call:
In the U.S.A. (800) 443-5853
In Canada (800) 36-FLUKE
From other countries +1 (425) 446-5500
www.fluke.com

©2023 Fluke Corporation.
Specifications subject to change without notice.
01/2023

**Modification of this document is not permitted
without written permission from Fluke Corporation.**