



PRODUCT DESCRIPTION

REXCO 25 HIGH PERFORMANCE CHAIN LUBE is a product used to lubricate chains, be it on motorbikes, bicycles, industrial machinery, or other equipment that uses chains as part of its driving mechanism. Chain lubricants serve to reduce friction between chain parts, thereby extending chain life, reducing wear, and reducing noise. **REXCO 25 HIGH PERFORMANCE CHAIN LUBE** also help in keeping the chain moving smoothly and efficiently, and prevent rust and corrosion.

REXCO 25 HIGH PERFORMANCE CHAIN LUBE In applying chain lubricant, it is important to clean the chain from dirt and dust so that the lubricant can work optimally. **REXCO 25 HIGH PERFORMANCE CHAIN LUBE** Keep going in extreme conditions with a high formulation. Designed for dry and dusty, wet, muddy & extreme conditions, provides a durable coating by repelling water and mud while protecting your chain to extend its life.

PRODUCTS



120 ML

350 ML

PRODUCT APPLICATIONS

- Motorcycle
- Bicycle
- Chainsaw
- Chain Drive
- Gear Machine
- Forklift
- Industrial Crane
- O, X, Z Ring

ADVANTAGES & FEATURES

- **REXCO 25 HIGH PERFORMANCE CHAIN LUBE** Product does not contain chlorofluorocarbons (CFCs), (HCFCs).
- **REXCO 25 HIGH PERFORMANCE CHAIN LUBE** Product does not contain Lead (Pb), Mercury (Hg), Cadmium (Cd), Hexavalent Chromium (Cr6), Polybrominated biphenyls (PBB), or Polybrominated diphenylether complying of the RoHS certificate.
- Quality testing involves a third party that has obtained ISO/IEC 17052 certificate.
- High loading chain lubrication.
- Prevent oxidation and extends chain life.
- High water resistance.
- Eliminates creaking sounds, anti sling formula, and anti wear.
- Contains anti rust and high quality synthetic oil.
- Special for automotive and industry chain.

DIRECTIONS FOR USE

- Shake the canister well before use.
- Test compatibility with plastics and rubbers and painted surface prior application.
- Hold the can and apply from a distance of 15-20 cm. Apply the components thoroughly and paying particular attention to the seized contact areas.
- In same severe cases, apply **REXCO 25 HIGH PERFORMANCE CHAIN LUBE** for second time after several minutes may be beneficial.
- Use 360° valve, can be sprayed in any direction.
- Save to use on fabric, plastic, paint, and other finishes.
- **CAUTIONS** : Pressurized container, protect from sunlight, do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not spray on naked flame or any incandescent material. Do not breathe spray. Avoid contact with the skin.
- **KEEP OUT OF THE REACH OF CHILDEN.** Contains distillates (petroleum), hydro treated light.

TECHNICAL DATA TEST

PARAMETERS	UNITS	TYPICAL DATA	METHODS
Appearance	-	Amber Transparent Liquid	Visual
Odour	-	Mild Odour	-
Solubility In Water	-	Not Soluble	-
Specific Gravity At 27 °c	-	0.86-0.92	Astm D4052-11
Color Astm	No. ASTM	L 3.0	Astm D1500-12
Kinematic Viscosity At 27 °c	cSt	-	Astm D445-14
Boiling Point	°C	> 90	Astm D1120-11
PH	-	N/A	-
Flash Point COC	°C	> 15	Astm D92-12