Flexible Conduit



FEATURES

- IP40 performance
- Highly Flexible
- High mechanical strength
- -100°C to +300°C
- Manufactured to BS EN 61386

RS PRO Galvanised Steel Flexible Conduit 20mm – 30 metres

RS Stock No.: 2149588



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

Flexible Conduit



General Specifications

| Material | Galvanised Steel | | | |
|-------------------------------|------------------|--|--|--|
| Colour | Self Colour | | | |
| Conduit Type | Flexible | | | |
| IP Rating | IP40 | | | |
| Length | 30 m | | | |
| Maximum Operating Temperature | +300°C | | | |
| Minimum Operating Temperature | -100°C | | | |
| Nominal Diameter | 20mm | | | |
| Internal Diameter (ID) | 16.8mm | | | |
| Outside Diameter (OD) | 20.3mm | | | |

Compatible Glands

| Stock No. | Brand | Product Name | Attribute 1 | Attribute 2 | Attribute 3 |
|-----------|--------|---------------------|--------------|--------------------------------|---------------------|
| 2149559 | RS PRO | NPB Fixed Gland | 2 part gland | High mechanical strength | -100°C to +300°C |
| 2149560 | RS PRO | NPB Swivel Gland | 2 part gland | High mechanical strength | -100°C to +300°C |