

FEATURES

- **Material:** UL approved Nylon 66, 94V-2
- **Color:** Grey (RAL7001) available in other colors.
- **Suit a variety of applications, and diverse industries.**
- **Function :**Mount gland to pre-drilled panel hole, use locknut to fix gland on board, insert the cables in the seal, and then tighten up the nut to hold cables in position.
- **Simply and quickly fixed, high degree of the protection IP68 preventing dust and water.**

RS PRO Cable Gland

RS Stock No.: 214-1063



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

- Material: UL approved Nylon 66, 94V-2
- Color: Grey(RAL7001), available in other colors.
- Suit a variety of applications, and diverse industries.
- Function :Mount gland to pre-drilled panel hole, use locknut to fix gland on board, insert the cables in the seal,and then tighten up the nut to hold cables in position.
- Feature : Simply and quickly fixed, high degree of the protection IP68 preventing dust and water.
- Available to order the accessories separately. Follow the drawing and add the letter to the suffix part number,L for locknut, W for washer, B for gland body, S for seal, N for nut.

General Specifications

Series	Metric Thread
Type	Cable Gland
Colour	Grey(RAL7001)
Material	Nylon 66
Finish	
Application	
Resistant To	
UV Resistant	No
Minimum Operating Temperature	-40°C
Maximum Operating Temperature	85°C
Fire Behaviour	Self-Extinguishing
Quantity	10pcs

Mechanical Specifications

Thread	M12 x P1.5
Mounting Hole	12.0~12.3 mm
Cable Range	3~ 6.5 mm

Protection Category

IP Rating

IP68

Approvals

Declarations

Standards Met

UL, RoHS, CE, IP68, HF

Similar Products

Stock No.	Brand	Product Name	Colour	Material	Thread
669-4689	RS PRO	Cable Gland	Black	Nylon 66	M40 x P1.5
669-4670	RS PRO	Cable Gland	Black	Nylon 66	M32 x P1.5



RS Article	Thread	Mounting Hole	D1	D2	B1	L1	L2	L3	Cable Range	Packing
2141063	M12xP1.5	12.0~12.3	12	7.3	6.5	8	19.7	12.7	3 ~ 6.5	10PCS

