



Datasheet

RS PRO 7/16 4 HOLE FLANGE MOUNT JACK - JACK ADAPTER

JACK - JACK ADAPTER

Stock number: 170-6998

EN

NO	DESCRIPTION	DATE	
△	2700 → 1400	12.12.18 ⁷	

1.0 ELECTRICAL

1.1 FREQUENCY RANGE: DC-7.5 GHz
 1.2 NOMINAL IMPEDANCE: 50 OHMS
 1.3 VOLTAGE RATING: 1400 VOLTS MAX. △
 1.4 VSWR: 1.05 MAX. @2 GHz
 1.5 MAX. #7.5 GHz

2.0 MATERIALS

2.1 BODIES: BRASS PER JIS-C3604
 2.2 CENTER CONTACT: BERYLLIUM COPPER PER ASTM B196 UNS C17800
 2.3 INSULATION: TEFLON PER ASTM D1487 AND ASTM D1710

3.0 FINISHES AND OTHERS

3.1 SEE BELOW TABLE FOR DETAILS.

4.0 MECHANICAL

4.1 INTERFACE IN ACCORDANCE WITH: IEC 168-4

5.0 ENVIRONMENTAL

5.1 OPERATING TEMPERATURE RANGE: -55° C TO +155° C

APPROVED by _____ DATE: _____

DESCRIPTION	7/16 4 HOLE FLANGE MOUNT JACK-JACK ADAPTER		
製圖	品名	DATE	REV.
DRAWN	Army	X	01.04.18 ⁷ 版 A-1
CHECK	Jenny	XX	
繪圖	單位	TITLE \ ROHS COMPLIANT (500)期	
總定	比例	DWG.NO: 62-0010-Z	
	SCALE		
	ANGLE	3:1	

NO	DESCRIPTION	MATERIAL	QTY	FINISH
5	CHASSIS	BRASS	1	WHITE BRONZE 60μ MIN.
4	CENTER CONTACT	BERYLLIUM COPPER	1	SILVER 70μ MIN.
3	INSULATION	TEFLON	1	NONE
2	BODY	BRASS	1	WHITE BRONZE 60μ MIN.
1	CENTER CONTACT	BERYLLIUM COPPER	1	SILVER 70μ MIN.