

Datasheet

Zinc Plated Throughbolts

Product

The Throughbolt is a torque controlled anchor suitable for use in concrete over C20/25

Material


Carbon Steel

Standard colour

Yellow

Finish

Zinc Plated and Yellow Passivated min 5µm



| Part Number | Anchor/ Hole Size | Anchor Length | Thread Length | Maximum Fixture Thickness | Minimum Hole Depth | Rec. Tensile Resistance | Rec. Shear Resistance | Tightening Torque |
|----------------|----------------------|------------------|------------------|---------------------------------|--------------------------|-------------------------------|-----------------------------|----------------------|
| | Α | В | С | | | | | |
| | mm | mm | mm | mm | mm | kN | kN | Nm |
| 9086949 | 6 | 55 | 30 | 15 | 34 | 2.2 | 2.4 | 6 |
| 9086943 | 8 | 50 | 20 | 5 | 40 | 2.9 | 3.5 | 10 |
| 9086952 | 8 | 65 | 35 | 20 | 40 | 2.9 | 3.5 | 10 |
| 9086955 | 8 | 80 | 50 | 35 | 40 | 2.9 | 3.5 | 10 |
| 9086959 | 8 | 100 | 70 | 55 | 40 | 2.9 | 3.5 | 10 |
| 9086968 | 8 | 130 | 85 | 85 | 40 | 2.9 | 3.5 | 10 |
| 9086961 | 10 | 65 | 25 | 8 | 50 | 4.4 | 5.4 | 28 |
| 9086965 | 10 | 75 | 35 | 18 | 50 | 4.4 | 5.4 | 28 |
| 9086974 | 10 | 120 | 80 | 63 | 50 | 4.4 | 5.4 | 28 |
| 9086977 | 12 | 80 | 30 | 5 | 65 | 7.0 | 8.4 | 34 |
| 9086971 | 12 | 100 | 50 | 25 | 65 | 7.0 | 8.4 | 34 |
| 9086980 | 12 | 120 | 70 | 45 | 65 | 7.0 | 8.4 | 34 |
| 9086983 | 12 | 140 | 90 | 65 | 65 | 7.0 | 8.4 | 34 |
| 9086987 | 16 | 150 | 90 | 55 | 85 | 9.4 | 14.3 | 85 |
| 9086996 | 16 | 175 | 90 | 80 | 85 | 9.4 | 14.3 | 85 |
| 9086999 | 16 | 220 | 90 | 125 | 85 | 9.4 | 14.3 | 85 |



