

FEATURES

- Cartridge heaters have high temperature lead wires that can stand temperature of up to 450°C
- High impact ceramic cap
- Deep holes in ceramic cap prevents fraying of lead
- Nickel-chromium resistance wire
- TIG welded end disc
- Fiberglass lead wire insulation
- 10in Lead wires
- RoHS-compliant for restricted hazardous substances

Heating Element, 150mm, 300 W, 220 V ac

RS Stock No.: 860-6899



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

Use this tubular cartridge heater from RS PRO for all your industrial heating needs, from plastics and packaging applications to hot stamping and printing. Its fibreglass-insulated lead wire is able to handle temperatures up to +450°C.

General Specifications

Max Operating Temp	450°C
Sheath Material	304 Series stainless steel
Applications	Dies, Moulds, Platens, Heat Sealing, labelling, Packaging, Hot Melt Adhesive Machinery

Electrical Specifications

Power Rating	300W
Supply Voltage	220VAC
Lead Wire Insulation	Fibreglass

Mechanical Specifications

Lead Length	10in
Diameter	10mm
Length	150mm

Tolerance Specifications

Diameter Tolerance	9.86mm to 9.98mm
---------------------------	------------------

Approvals

Compliance/Certifications	RoHS Compliant
---------------------------	----------------



Standard Features and Internal Construction:-



1. High temperature lead wires for temperatures up to 450° C.
2. High impact ceramic cap retards contamination and is suitable for high vibration applications. Deep holes in cap prevent fraying of leads when bent.
3. Nickel-chromium resistance wire for maximum heater life, evenly wound for even heat distribution.
4. High purity magnesium oxide fill selected for maximum dielectric strength and thermal conductivity, highly compacted for maximum heat transfer.
5. 304 stainless steel sheath for oxidation resistance in a wide variety of environments. 316 stainless steel and Incoloy are also available. Please consult the application guide in the back for help in determining which material is best for your application.
6. TIG welded end disc to prevent contamination and moisture absorption.