


Art.no. **4400**
Art.no. **4400/4**



Lever action grease gun, suitable for the use with bulk grease or with grease cartridges. With plastic flexible outlet hose \varnothing ext. 8 mm x 300 mm length, M 10x1, and 4 – jaws – hydraulic coupler. Suitable for grease up to a viscosity of NLGI 2.

Art. no.	Max delivery	Max outlet pressure	Capacity grease cartridge	Diameter suitable grease cartridge	Length suitable grease cartridge	Weight	Dimensions (LxWxH) (mm)
4400	1.2	300 bar	600 g	56 mm	300 mm	1.70 kg	150x60x480
4400/4	cm ³ /stroke	400 bar	400 g	52 mm	240 mm	1.70 kg	110x60x370




Art.no. **4450**
Art.no. **4450/4**



Pneumatic grease gun, suitable for the use with bulk grease or with grease cartridges. With plastic flexible outlet hose \varnothing ext. 8 mm x 300 mm length, M 10x1, and 4 – jaws – hydraulic coupler. It is a single action mechanism (non-continuous grease supply): when activating the trigger, the internal piston moves and supplies grease; when the trigger is released, the piston returns in its initial position. By repeating this procedure the grease can be dispensed. Compressed air pressure: 4 – 8 bar. Suitable for grease up to a viscosity of NLGI 2.

Art. no.	Max delivery	Max outlet pressure	Capacity grease cartridge	Diameter suitable grease cartridge	Length suitable grease cartridge	Weight	Dimensions (LxWxH) (mm)
4450	1.2	300 bar	600 g	56 mm	300 mm	2 kg	240x70x550
4450/4	cm ³ /stroke	300 bar	400 g	52 mm	240 mm	2 kg	240x70x470



Art.no. **4450/C**



Pneumatic grease gun with a continuous grease flow, suitable for the use with bulk grease or with grease cartridges. With rigid outlet pipe 150 mm length, M 10x1, and 4 – jaws – hydraulic coupler.

Compressed air pressure: 2 – 8 bar. Suitable for grease up to a viscosity of NLGI 2.

Art. no.	Max delivery	Max outlet pressure	Capacity grease cartridge	Diameter suitable grease cartridge	Length suitable grease cartridge	Weight	Dimensions (LxWxH) (mm)
4450/C	0.8	400 bar	400 g	52 mm	240 mm	2 kg	170x75x400



Art.no. **4408**



One-hand-operated grease gun, professional version, suitable for the use with bulk grease or with grease cartridges.

With plastic flexible outlet hose \varnothing ext. 8 mm x 300 mm length, M10x1, and 4 – jaws – hydraulic coupler. The grease gun can be used in a “high volume” or in a “high pressure” mode.

Art. no.	Max delivery	Max outlet pressure	Capacity grease cartridge	Diameter suitable grease cartridge	Length suitable grease cartridge	Weight	Dimensions (LxWxH) (mm)
4408	1.1	200 bar	400 g	52 mm	240 mm	1.6 kg	165x66x400
	0.8	300 bar					



Art. no. **4405** Cartridge with lithium grease, NLGI 2, with 600 g capacity. Diameter 56 mm, length 300 mm. Kinematic viscosity of the basing oil: 150 cSt, 40°C. Temperature range of use: -20°C - +120°C. According to DIN 51502 K 2 K-20. Packaging unit: 15 pcs.



Art. no. **4406** Cartridge with lithium grease, NLGI 2, with 400 g capacity. Diameter 52 mm, length 235 mm. Kinematic viscosity of the basing oil: 150 cSt, 40°C. Temperature range of use: -20°C - +120°C. According to DIN 1284. Packaging unit: 15 pcs.