



ENGLISH

Datasheet

RS PRO KHA-0760 is a tool for crimping insulated heat shrink connectors, 0.5 - 6.0 mm²/AWG 22- 10 (red, blue and yellow insulations).

Stock No: 2080636





Features & Benefits:

- High strength, through hardened alloy steel construction
- Unique mechanism significantly reduces hand force
- Versatile and easy to use for right hand or left hand users.
- Non-slip pad holds tool in place when leveraging on a work surface
- Full cycle crimp mechanism to ensure consistent, reliable crimp
- Ratchet release mechanism to clear miss-crimps and obstructions
- Precision eccentric adjustment for consistent performance and ability to calibrate
- Hole in handle allows attachment of safety strap
- Each tool has a unique serial number for traceability

Crimp Die Set

Crimp Profile





TECHNICAL DATA

Length: 256 mm/10.08"

Width: 22 mm/0.87" Height: 80 mm/3.15" Weight: 558 gr/1.23 lb

Wire size: 0.5-6 mm² / AWG 22-AWG 10

Crimp dimensions mm/mm2:

 $0.50 - 1.5 \text{ mm}^2/1.5 - 2.5 \text{ mm}^2/4 - 6 \text{ mm}^2$

Crimp dimensions inch/AWG:

AWG 22 - AWG 16/AWG 16 - AWG 14/AWG 12 - AWG 10

Connector: Heat shrink connectors

Description: For pre insulated red ,blue and yellow heat shrink

connectors.

Life span, cycles: 50,000



