

4mm Male Banana Plug to Plug **multicomp** PRO




Applications

To connect to 4mm banana jacks, sockets and binding posts. Very low voltage general purpose electric testing, controlling and measuring.

Specifications

- Electrical Safety : Very low voltages only: 33V AC / 70V DC, 12A (at +40°C)
- Operating Temperature : -20°C to +80°C
- Materials : Conductors: Nickel-coated brass and red annealed copper.
Wire jackets: PVC or silicone. Insulators and lantern contact spring
- Colour : Black and Red
- Length : 0.25 meters (25cm), 0.5 meters (50cm) & 1 meters (100cm).

Diagram



The design and the material of the lantern contact springs meet the need of low resistance and reliability.

European Union marking.

The wire attachments comply with heavy duty.

Current marking.

Double jacket wire to offer a wire wear indicator. Cross section area 0.75 mm². Lengths 25cm, 50cm, 100cm (visible length of the wire, not the overall length of the lead).

The 4mm banana male connections comply with the 4mm banana sockets meet the requirements of interchangeability dimensions of the standard NF C 93-440:1986.

Part Number Table

Description	Colour	Length	Part Number
Straight 4mm Male Banana Plug to Straight 4mm Male Banana Plug Lead	Black	0.25m	76-094
	Red		76-095
	Black	0.5m	76-096
	Red		76-097
	Black	1m	76-112
	Red		76-114

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.