

FEATURES

- Galvanised steel wire outer covering
- High tensile steel wire reinforcing
- Suitable for mineral oils, lubricating oils, water glycol, water-oil emulsion, hydraulic fluids

RS PRO Hydraulic Hose Assembly

RS Stock No.: 2509136



500 mm Galvanised Steel Wire
Hydraulic Hose Assembly

Product Description

Part No.	Length	End Fittings	Pack Qty.
2509136	500 mm	Straight G 1/4" Female	5

Features

- Galvanised steel wire outer covering
- High tensile steel wire reinforcing
- Suitable for mineral oils, water glycol, water-oil emulsion, hydraulic fluids

General Specifications

Connector A – Angle	Straight
Connector A – Gender	Female
Connector A – Thread Size	1/4"
Connector A – Thread Standard	G
Connector A	Straight G 1/4" Female
Connector B – Angle	Straight
Connector B – Gender	Female
Connector B – Thread Size	1/4"
Connector B – Thread Standard	G
Connector B	Straight G 1/4" Female
Cover Material	Galvanised Steel Wire
Inner Hose Material	Synthetic Rubber
Inside Diameter	1/4"
Max. Operating Pressure	190 bar
Max. Operating Temperature	+121°C
Min. Operating Temperature	-40°C
Overall Length	500 mm
Reinforcing Material	Steel
Standard Met	RoHS Compliant