

Features

- Standard to DIN 867, DIN 3962, DIN 3963, Grade 9 or equivalent
- Standard tolerances, unless otherwise stated 0.25mm
- Steel EN8 (080M40/080M46)

RS PRO Metric Spur Gears in Steel 1.0 MOD

RS Stock No.: see below table



RS PRO Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

Product Description

The RS PRO metric steel spur gear:

- Standard to DIN 867, DIN 3962, DIN 3963, Grade 9 or equivalent
- Standard tolerances, unless otherwise stated 0.25mm
- Steel EN8 (080M40/080M46)

Products Range

RS Article no.	Type	No. of Teeth	Pitch \emptyset dp	Bore \emptyset H8	Hub/Boss \emptyset dm	Outside \emptyset de	O/A Width A	Face Width B
1827801	B	12	12	5	9	14	25	15
1827802	B	13	13	5	10	15	25	15
1827803	B	14	14	6	10	16	25	15
1827804	B	15	15	6	12	17	25	15
1827805	B	16	16	6	13	18	25	15
1827807	B	18	18	8	15	20	25	15
1827808	B	20	20	8	16	22	25	15
1827809	B	22	22	8	18	24	25	15
1827810	B	24	24	8	20	26	25	15
1827811	B	25	25	8	20	27	25	15
1827813	B	26	26	8	20	28	25	15
1827814	B	28	28	8	20	30	25	15
1827815	B	30	30	8	20	32	25	15
1827816	B	32	32	10	25	34	25	15
1827817	B	35	35	10	25	37	25	15
1827818	B	36	36	10	25	38	25	15
1827819	B	40	40	10	25	42	25	15
1827820	B	45	45	10	30	47	25	15
1827821	B	48	48	10	30	50	25	15
1827822	B	50	50	12	30	52	25	15
1827823	B	55	55	12	40	57	25	15
1827824	B	60	60	12	40	62	25	15
1827825	B	70	70	12	50	72	25	15
1827826	B	80	80	12	50	82	25	15

- Standard : to DIN 867, DIN 3962, DIN 3963, Grade/Quality 9 or Equivalent
- Standard tolerances, unless otherwise stated $\pm 0.25\text{mm}$.
- All dimensions in mm
- Steel EN8, (080M40/080M46) or equivalent

