

# Embedded Switch Mode Power Supplies (SMPS)


## FEATURES

- Universal 85 - 264V AC Active PFC
- Compact size: 4" × 2" × 1"
- Efficiency up to 95%
- Stand-by power consumption. < 0.5W
- Operating temperature range - 40°C to +70°C
- Conformally coated PCB
- Low leakage current < 0.1mA
- Output short circuit, over-current, over-voltage protection.
- EMI performance meets. CISPR32 / EN55032 CLASS B
- Medical and Industrial safety approvals. Suitable for BF application

IEC/EN/UL62368-1,  
IEC/EN60335-1,  
IEC/EN61558-1, GB4943-1,  
IEC/EN60601-1 (2 × MOPP)

## RS PRO Embedded Switch Mode Power Supplies

- **2336881**
- **2336883**
- **2336886**



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

# Embedded Switch Mode Power Supplies (SMPS)

## Product Description

AC-DC open frame power supply suitable for a wide range of Industrial, Medical and Dental applications. Featuring a universal AC input this cost-effective, high density design is available in a range of standard outputs. Complying with International and European EMC and safety standards IEC/EN/UL62368, GB4943, IEC/EN60335, IEC/EN61558, IEC/EN60601

## General Specifications

<b>Model</b>	AC-DC 225W Medical / Industrial power supply
<b>Mounting Type</b>	Chassis Mount
<b>MTBF</b>	MIL-HDBK-217F@25°C > 300,000 h
<b>Applications</b>	Industrial control systems, instrumentation and medical equipment

RS Stock#	Input Voltage	Output Voltage	Adj'range (V)	Output Current	Wattage	Efficiency (Typ)
2336881	85 to 264V ac 120 to 370V dc	12V DC	11.8-12.6	11.67A (Free air)	140W	93%
				18.75A (13CFM)	225W	
2336883	85 to 264V ac 120 to 370V dc	24V DC	23.5-25.2	5.83A (Free air)	140W	94%
				9.4A (13CFM)	225W	
2336886	85 to 264V ac 120 to 370V dc	48V DC	47.1-50.4	2.91A (Free air)	120W	94%
				4.7A (13CFM)	225W	

## Input Specifications

Input Specification	
<b>Voltage Range</b>	85 to 264V ac, 120 to 370V dc
<b>Frequency</b>	47 to 63Hz
<b>AC Current Rating</b>	3A/115V ac, 2A/230V ac
<b>Inrush Current</b>	40A/ 115V ac, 75A / 230V ac
<b>Leakage</b>	<0.1mA, single fault <0.5mA
<b>Power Factor</b>	0.99 115Vac, 0.95 230Vac
<b>Standby power consumption</b>	0.5W

# Embedded Switch Mode Power Supplies (SMPS)

## Output Specifications

Output Specification			
Output voltage	12V	24V	48V
Adjustment range	11.8-12.6V	23.5-25.2V	47.1-50.4V
Rated Current (13CFM)	18.75	9.4A	4.7A
Ripple & Noise (max.) *	60mVp-p	100mV	200mV
Rated Power (13CFM)	225W	225W	225W
Line Regulation typ.	±0.5%	±0.5%	±0.5%
Load Regulation typ.	±0.5%	±0.5%	±0.5%
Max Capacitive load $\mu$ F	6000 $\mu$ F	3200 $\mu$ F	1600 $\mu$ F
Minimum Load	0%	0%	0%
Fan Power	12V 0.5A with output voltage accuracy $\pm$ 15%		

Hold Up Time	16ms/230V ac
Over Voltage Protection	12V output $\leq$ 16V (Output voltage turn off, re-power on for recover)
	24V output $\leq$ 32V (Output voltage turn off, re-power on for recover)
	48V output $\leq$ 60V (Output voltage turn off, re-power on for recover)
Over-current Protection	$\geq$ 130% Io, hiccup, self-recovery
Short Circuit Protection	Hiccup, continuous, self-recovery
Isolation	4KVAC

Notes: 1. \*Output voltage accuracy: including the setting error, line regulation, load regulation. 2. \*The "Tip and barrel method" is used for ripple and noise test, output parallel 10 $\mu$ F electrolytic capacitor and 0.1 $\mu$ F ceramic capacitor, please refer to AC-DC Converter Application Notes for specific information. 3. \*When the product works at light load ( $\leq$ 15% IO), in order to improve the efficiency to reach at green working mode, the value of ripple and noise will be double. 4. \*For all the above test items, please refer to our company standard "AC-DC Black Box Test Specification" for specific test specifications and methods


# Embedded Switch Mode Power Supplies (SMPS)

## General Specifications

Item	Operating Conditions			Min	Typ	Max.	Unit
Isolation	Input-output	Electric Strength Test for 1min, leakage current <10mA		4000	-	-	VAC
	Input-Earth	Electric Strength Test for 1min, leakage current <10mA		1500	-	-	
	Output-Earth	Electric Strength Test for 1min, leakage current <5mA		1500	-	-	
Insulation Resistance	Input-Earth	500VDC, 25±5 °C,		50	-	-	MΩ
	Input-output	Humidity < 95%RH, non-condensing		50	-	-	
	Output-Earth	500VDC		50	-	-	
Isolation level	Input-output			2 × MOPP			
	Input-Earth			1 × MOPP			
	Output-Earth			1 × MOPP			
Operating Temperature				-40	-	+70	°C
Storage Temperature				-40	-	+85	
Storage Humidity	Non-condensing			10	-	95	%RH
Operating Humidity				20	-	90	
Power Derating	Operating temperature derating	Air cooling	+45 °C to +70 °C	2.0	-	-	% / °C
		13CFM	+50 °C to +70 °C	2.5	-	-	
			-40 °C to -30 °C	2.0	-	-	
	Input voltage derating	85-115VAC		1.0	-	-	%/VAC
Safety Standard				Meet IEC/EN/UL62368-1 EN60335-1 IEC/EN61558-1, GB4943-1 IEC/EN60601-1/ES60601-1(3.1 version) CAN/CSA-C22.2 No.60601-1:14-Edition			
Safety Certification				IEC/EN/UL62368-1 EN60335/EN61558/ EN60601			
Safety Class				CLASS I (PE and must be connected)			
MTBF	MIL-HDBK-217F@25°C			> 300,000 h			

# Embedded Switch Mode Power Supplies (SMPS)

## Derating



## EMC Specifications

Emissions	CE	CISPR32/EN55032 CLASS B	
	RE	CISPR32/EN55032 CLASS B	
	Harmonic Current	IEC/EN61000-3-2 CLASS D	
Immunity	ESD	IEC/EN 61000-4-2 Contact ±8KV/Air ±15KV	Perf. Criteria A
	RS	IEC/EN 61000-4-3 10V/m	Perf. Criteria A
	EFT	IEC/EN 61000-4-4 ±4KV	Perf. Criteria A
	Surge	EC/EN 61000-4-5 ±2KV/±4KV	Perf. Criteria A
	CS	IEC/EN61000-4-6 10 Vr.m.s	Perf. Criteria A
	Voltage dips, short interruptions and voltage variations immunity	IEC/EN61000-4-11 0%, 70%	Perf. Criteria B


Note: 1.\*The power supply should be considered as a part of the components in the system. All EMC performance has been tested on a metal plate with a thickness of 1mm and a length of 360mm × 360mm. The power supply must be combined with the terminal equipment for electromagnetic compatibility confirmation. 2.\*Category I products with PE (which must be connected)

# Embedded Switch Mode Power Supplies (SMPS)


## Mechanical Specifications

Case Material	Open Frame
Dimensions	101.6 x 50.8 x 25.4mm
Weight	175g (Typ.)
Cooling Method	Air cooling / 13CFM

## Dimensions and recommended layout




THIRD ANGLE PROJECTION



Pin-Out			
Pin	Function	Product Connector	Customer Connector
1	AC(N)/DC-	JST B3P-VH or equivalent	Housing: JST VHR Terminal: JST SVH-21T-P1.1 or equivalent
2	NC		
3	AC(L)/DC+		
4	Fan-	JST B2B-PH-K-S or equivalent	Housing: JST PHR-2 Terminal: JST SPH-002T-P0.5S or equivalent
5	Fan+		
6, 7, 8	-Vo	JST B6P-VH or equivalent	Housing: JST VHR Terminal: JST SVH-21T-P1.1 or equivalent
9, 10, 11	+Vo		

Position	Screw Spec.	L(Recommend)	Torque(max)
① - ④	M3	6mm	0.4N·m



### Note:

- Unit: mm[inch]
- ADJ: Output adjustable resistor
- General tolerances:  $\pm 1.00$  [ $\pm 0.039$ ]
- Do not use fan power to power other devices
- The layout of the device is for reference only, please refer to the actual product
- Reserved safety distance between PCB edge and customer components, recommended 10mm
- Class I system ①, ③ positions must be connected to the earth (⊥)
- Class II system ①, ③ positions must be connected together

## Approvals

<b>Safety Standard</b>	IEC/EN/UL62368-1, EN60335-1, IEC/EN61558-1, GB4943-1, IEC/EN60601-1, ES60601-1(3.1 version), CAN/CSA-C22.2 No.60601-1:14-Edition 3, EN60601-1-2 Edition 4
<b>Safety Certification</b>	IEC/EN/UL62368-1, EN60335, IEC61558, UL/EN60601
<b>Safety Class</b>	Class I (PE and must be connected)

### Note:

1. Unless otherwise specified, parameters in this datasheet were measured under the conditions of  $T_a=25^{\circ}\text{C}$ , humidity<75%RH with nominal input voltage and rated output load.
2. All index testing methods in this datasheet are based on our company corporate standards.
3. In order to improve the efficiency at high input voltage, there will be audible noise generated, but it does not affect product performance and reliability.
4. Products are related to laws and regulations: see "Features" and "EMC".
5. Our products shall be classified according to ISO14001 and related environmental laws and regulations and shall be handled by qualified units.
6. CAUTION: Double pole, neutral fusing. Disconnect mains before servicing."/"/ ATTENTION: Double pôle/fusible sur le neutre. Débrancher l'alimentation avant l'entretien;
7. The power supply is considered a component which will be installed into a terminal.