

## FEATURES

- Material: Warp proof self-extinguishing UL approved PVC, 94V-0 flammability rating, M1 rating NF fire resistant test.
- Color: Black
- These devices are for routing of wires within devices in factory installations.
- Features parallel holes on both sidewalls to facilitate cutting in wire application.
- Special color, size, length upon request of reasonable quantity.

## RS PRO Wiring Duct

RS Stock No.: 2339167 2339171

2339173BK 2339174 2339178  
2339179



RS Professionally Approved Products bring to you professional quality parts across all product categories. Our product range has been tested by engineers and provides a comparable quality to the leading brands without paying a premium price.

## Product Description ATTRIBUTE 1

- Material: Warp proof self-extinguishing UL approved PVC, 94V-0 flammability rating, M1 rating NF fire resistant test.
- Color: Black
- Vicat softening point: 86°C
- UL Test up to 50°C
- These devices are for routing of wires within devices in factory installations.
- Features parallel holes on both sidewalls to facilitate cutting in wire application.
- Special color, size, length upon request of reasonable quantity.
  - Regular wiring duct cover can be upgrade to NON-SLIP ones which improves tightness between duct and cover, benefits vertical installations, and improves effectiveness and avoid cover slip off.

## General Specifications

|                                      |   |
|--------------------------------------|---|
| <b>Series</b>                        | Wiring Duct                                     |
| <b>Type</b>                          |   |
| <b>Colour</b>                        | Black   |
| <b>Material</b>                      | PVC   |
| <b>UV Resistant</b>                  | NO  |
| <b>Minimum Operating Temperature</b> | 0°C   |
| <b>Maximum Operating Temperature</b> | Vicat softening point: 86°C, UL Test up to 50°C |
| <b>Fire Behaviour</b>                | Self-Extinguishing                              |
| <b>Quantity</b>                      | 2M  |

## Mechanical Specifications

Unit:mm

| W x H (mm) | Slot | Wires to be Contained (16-14 AWG) | Length | Color |
|------------|------|-----------------------------------|--------|-------|
| 25x50      | 8    | 20 ~ 25 pcs                       | 2M     | Black |
| 25x75      |      | 60 ~ 75 pcs                       |        |       |
| 50x25      |      | 25 ~ 45 pcs                       |        |       |
| 75x50      |      | 180 ~ 200 pcs                     |        |       |
| 75x75      |      | 200 ~ 250 pcs                     |        |       |

## Approvals

|                      |               |
|----------------------|---------------|
| <b>Declarations</b>  |               |
| <b>Standards Met</b> | UL, CSA, RoHS |

## Similar Products

| Stock No. | Brand | Product Name | Colour | Material |
|-----------|-------|--------------|--------|----------|
|           |       |              |        |          |

