

ER8822

APC Easy Rack, 48U, Black, With Roof, Castors, Feet, 4 Brackets, and Side Panels, No Bottom, 2258H x 800W x 1200D mm



Overview

Lead time	Usually in Stock
-----------	------------------

Main

Product or component type	Rack enclosure
Number of rack unit	48U
Provided equipment	Baying hardware Key(S) Keyed-alike doors and side panels Leveling feet Mounting hardware Pre-installed casters Side panels

Physical

Height	225.8 cm
Width	80 cm
Depth	120 cm
Net weight	150 kg
Colour	Black
Mounting mode	Not rack-mountable
Maximum mounting depth	104.14 cm
Minimum mounting depth	24.16 cm
Rack width	19"
Marking	18 gauge front door 19 gauge rear door 16 gauge post 14 gauge EIA mounting rail
Permanent permissible load	1199.75 Kg static 599.65 kg dynamic

Conformance

Standards	UL 2416 UL 60950-1 EIA-310E
-----------	-----------------------------------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	239 cm
Package 1 Width	125 cm
Package 1 Length	85 cm
Package 1 Weight	159 kg
Pallet layers	1

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes

Contractual warranty

Warranty	5 year repair or replace
----------	--------------------------