



EN

Datasheet

RS PRO BATTERY MODULAR CONNECTORS SET 2x50 AMP CONTACTS+ 50 AMP 2-POLE HOUSING (GREY)

Stock number: 175-6961

HOUSING:

OPERATING TEMPERATURE RANGE: -20°C~ +125°C

MAXIMUM ELECTRICAL RATING: 600 VOLTS MAX.

HOUSING MATERIAL: POLYCARBONATE (PC)

SPRING MATERIAL: STAINLESS STEEL

CONTACT:

MAXIMUM ELECTRIC CURRENT:

A.W.G.


6

AMP.

95

CONTACT MATERIAL: COPPER





DESCRIPTION	DIMENSION inch(mm)			COLOR
	W	L	H	
HOUSING				
HOUSING WITH TWO SPRINGS, CAN BE USED WITH 50AMP SERIES CONTACTS	1.374 34.9	1.89 48	0.626 15.9	GREY

WIRE RANGE A.W.G. mm ²	DESCRIPTION	DIMENSION inch(mm)			
		L	E	d1	D
6 A.W.G. 14 mm ²	CONTACT TWO CONTACTS WITH ONE 50 AMP SERIES HOUSING	1.169 29.7	0.472 12.0	0.220 5.6	0.280 .71