

Benefits

- No external driver required which facilitates easy installation and maintenance
- Delivers uniform light distribution
- IP44 rated diffuser versions for damp locations such as bathrooms and kitchens

Application



Model	Item Description	W	PF	lm	lm/W	CRI	BA	Beam	Single Box (LxWxH)mm	Outer Box (LxWxH)mm	Packing Qty (PCS/CTN)
F26200RC-d/WH	SIENA 5" R125 13W 6500K DIM 90D WH	13.0	0.9	950	73	80	90°	25000	150*150*100	480*320*440	24

Technical Specifications	
CRI	80
Colour Consistency (SDCM)	≤ 6
Dimmable	Yes
Housing Colour	White
IP	IP44
IK	IK02
Driver integrated (Yes/No)	Yes


Electrical Supply	
Frequency (Hz)	50/60Hz
Voltage (V)	220V-240V
AC/DC	AC

Mechanical Properties	
Optical Material	PP
Housing Material	PC

Application Conditions	
Operating Temperature	-20°C~40°C
Application Temperature	20°C
Storage Environment	-20°C~40°C


Photometric Data

F26200RC-d/WH



m	Lux	Ø cm
0.5	2040	100
1	510	200
1.5	227	300
2	128	400
Beam angle = 90°		

Dimensional Drawing



F26200RC-d/WH