# multicomp PRO



#### Features:

- Fast Switching Speed
- Surface Mount Package Ideally Suited for Automatic Insertion
- For General Purpose Switching Applications
- High Conductance





Applications: High speed switching application

## Max. Rating @ T<sub>A</sub> = 25°C unless otherwise specified

| Parameter  | Symbol             | Limits      | Unit |
|--|--------------------|-------------|------|
| Peak repetitive peak reverse voltage<br>Working peak reverse voltage<br>DC reverse voltage | Vrrm<br>Vrms<br>Vr | 75          | V    |
| Forward continuous current   | Іғм                | 200         | mA   |
| Power dissipation  | Po                 | 225         | mW   |
| Operating junction temperature range   | Тј                 | 150         | °C   |
| Operating and storage temperature range  | Тята               | -55 to +150 | °C   |


## Electrical Characteristics @ T<sub>A</sub> = 25°C unless otherwise specified

| Parameter                 | Symbol                   | Conditions   | Min. | Max.                        | Unit |
|---------------------------|--------------------------|--|------|-----------------------------|------|
| Reverse breakdown voltage | Vr(br)                   | IR = 100μΑ   | 75   | -                           | V    |
| Forward voltage           | VF1<br>VF2<br>VF3<br>VF4 | IF = 1mA<br>IF = 10mA<br>IF = 50mA<br>IF = 150mA             | -    | 715<br>855<br>1,000<br>1250 | mV   |
| Reverse current           | lr                       | V <sub>R</sub> = 75V   | -    | 2.5                         | μA   |
| Diode capacitance         | Ср                       | VR = 0V, f = 1MHz  | -    | 20                          | pF   |
| Reverse recovery time     | trr                      | $I_{F} = I_{R} = 10 \text{mA}$ $V_{R} = 5V, R_{L}=100\Omega$ | -    | 4                           | ns   |

Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro








Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro




#### Plastic surface mounted package



|   |        | SOT-23     |        |
|---|--------|------------|--------|
|   | Dim    | Min        | Max    |
| ٦ | A      | 2.85       | 2.95   |
|   | В      | 1.25       | 1.35   |
|   | С      | 1 Tyj      | oical  |
|   | D      | 0.37       | 0.43   |
|   | E      | 0.35       | 0.48   |
|   | G      | 1.85       | 1.95   |
|   | Н      | 0.02       | 0.1    |
|   | J      | 0.1Ty      | /pical |
|   | K      | 2.35       | 2.45   |
|   | All Di | mensions i | n mm   |
|   |        |            |        |

#### **Soldering Footprint**



### **Package Information**

| Device      | Package | Shipping            |
|-------------|---------|---------------------|
| MMBD914-7-F | SOT-23  | 3,000 / Tape & Reel |

#### **Part Number Table**

| Description                | Part Number |
|----------------------------|-------------|
| High-Speed Switching Diode | MMBD914-7-F |

Important Notice : This data sheet and its contents (the "Information") belong to the members of the AVNET group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. Multicomp Pro is the registered trademark of Premier Farnell Limited 2019.

Newark.com/multicomp-pro Farnell.com/multicomp-pro Element14.com/multicomp-pro

