



Main

Range	Pragma
Product or component type	Enclosure
Enclosure type	Distribution enclosure
Width	426 mm outside:
Height	750 mm
Depth	125 mm
Nb of 18 mm modules per row	18
Nb of horizontal rows	4
Electrical insulation class	Double insulation Class II
Provided equipment	1 x identification label 1 x marking kit 1 x blanking plate strip
Type of door	Without

Complementary

Enclosure mounting	Surface
9 mm pitches	36
Total number of 18 mm modules	72
Power dissipation in W	64 W
[In] rated current	125 A
[Ui] rated insulation voltage	400 V
Type of rail	DIN
Cable entry	Trunking Cable or tube Removable plates Cut-out plates
Enclosure material	Back part: technoplastic Front face: technoplastic
Colour	Enclosure: white (RAL 9016) Front face: white (RAL 9016)

Environment

Fire resistance	Back part: 650 °C Front face: 650 °C
IP degree of protection	IP30 without door IP40 with door
IK degree of protection	IK08 without door IK09 with door
Overvoltage category	II
Ambient air temperature for operation	-25...60 °C
Standards	IEC 60670-1 IEC 60670-24 IEC 61439-1 IEC 61439-3

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	13.5 cm
Package 1 Width	51.0 cm
Package 1 Length	83.0 cm
Package 1 Weight	5.25 kg
Unit Type of Package 2	P12
Number of Units in Package 2	13
Package 2 Height	105.0 cm
Package 2 Width	80.0 cm
Package 2 Length	120.0 cm
Package 2 Weight	80.25 kg