# Eaton NON-40

## Catalog Number: NON-40

Eaton Bussmann series NON fuse, Non current limiting, Light duty circuit locations, 40 A, Class H, Non-indicating, Ferrule end x ferrule end, 50 kAIC at 250 Vac|50 kAIC at 125 Vdc, Standard, 10, 250 V, 125 Vdc

#### General specifications

Exercise Purport Autor protection Casto on rule Control Control Control Control Control Product Name Eaton Bussmann series NON fuse UPC 051712101615 Product Height 0.81 in

Product Weight 0.01 lb

Compliances

CE Marked

Catalog Number NON-40 Product Length/Depth 3 in

Product Width 0.81 in

Warranty

Not Applicable



## Electrical rating

#### Amperage Rating

40 A

#### Interrupt rating

50 kAIC at 250 Vac 50 kAIC at 125 Vdc

#### Voltage rating

250 Vac, 125 Vdc

### Physical details

#### Packaging type

Standard

#### General information

Class

Class H

Connection Ferrule end x ferrule end

**Fuse indicator** 

Non-indicating

Quantity

10

Special features

Non current limiting

#### Resources

Catalogs

Bussmann series full line catalog 1007, section 01- low voltage branch circuit fuses

Bussmann series complete full line catalog no. 1007

#### Multimedia

Bussmann series Fuseology

Specifications and datasheets Eaton Specification Sheet - NON-40

Technical data sheets NON-40~BUSS ONE TIME FUSE

Technical service bulletins Datasheet - FNQ-30



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com © 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

Eaton.comAll other trademarks are© 2023 Eaton. All Rightsproperty of their respectiveReserved.owners.



Eaton.com/socialmedia