



Main

Range of product	Altivar
Product or component type	Communication module

Complementary

Range compatibility	Altivar Process ATV600 Altivar Machine ATV340 except Sercos drives Altivar Machine ATV320 Altivar 32 Altivar Process Modular Altivar Process ATV900
Communication port protocol	Link Layer Discovery Protocol PROFINET
Electrical connection	2 connectors RJ45, Ethernet
Transmission rate	100 Mbps
Display type	1 LED for MS (Module Status) 1 LED for NS (Network Status) 1 LED for TX/RX (Transmit/Receive port 1) 1 LED for TX/RX (Transmit/Receive port 2)
Bus profile	PROFIdrive
Net weight	0.3 kg

Environment

Standards	IEC 61800-7-201 (CiA 402)
-----------	---------------------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.600 cm
Package 1 Width	6.500 cm
Package 1 Length	8.900 cm
Package 1 Weight	63.000 g
Unit Type of Package 2	S03
Number of Units in Package 2	100
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	6.700 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
PVC free	Yes