



## Main

|                               |                         |
|-------------------------------|-------------------------|
| Range of product              | Harmony XB7             |
| Product or component type     | Pilot light             |
| Device short name             | XB7                     |
| Mounting diameter             | 22 mm                   |
| Sale per indivisible quantity | 10                      |
| Shape of signaling unit head  | Round                   |
| Cap/operator or lens colour   | Orange                  |
| Light source                  | LED                     |
| Bulb base                     | Integral LED            |
| [Us] rated supply voltage     | 230...240 V AC 50/60 Hz |
| Device presentation           | Monolithic product      |

## Complementary

|  |   |
|--|---|
| Height                                 | 29 mm   |
| Width                                  | 29 mm   |
| Depth                                  | 54 mm   |
| Terminals description ISO n°1          | (X1-X2)PL   |
| Net weight                             | 0.02 kg   |
| Device mounting                        | Fixing hole - diameter: 22.5 mm 22.3 +0.4/0 conforming to EN/IEC 60947-5-1  |
| Fixing center                          | >= 30 x 40 mm (support panel) metal - thickness: 1...6 mm<br>>= 30 x 40 mm (support panel) plastic - thickness: 2...6 mm  |
| Fixing mode                            | Fixing nut beneath head: 2...2.4 N.m  |
| Connections - terminals                | Screw clamp terminals, <= 2 x 1.5 mm <sup>2</sup> with cable end conforming to EN/IEC 60947-1<br>Screw clamp terminals, 1 x 0.22...2 x 2.5 mm <sup>2</sup> without cable end conforming to EN/IEC 60947-1   |
| Tightening torque                      | 0.8...1.2 N.m conforming to EN 60947-1  |
| Shape of screw head                    | Cross compatible with JIS No 1 screwdriver<br>Cross compatible with Philips no 1 screwdriver<br>Cross compatible with pozidriv No 1 screwdriver<br>Slotted compatible with flat Ø 4 mm screwdriver<br>Slotted compatible with flat Ø 5.5 mm screwdriver |
| [Ui] rated insulation voltage          | 250 V (pollution degree 3) conforming to EN/IEC 60947-1   |
| [Uimp] rated impulse withstand voltage | 6 kV conforming to EN/IEC 60947-1   |
| Signalling type                        | Steady  |
| Supply voltage limits                  | 195...264 V AC  |
| Current consumption                    | 16...20 mA  |
| Service life                           | 70000 h at rated voltage and 25 °C  |







## Environment

|                                       |   |
|---------------------------------------|---|
| Protective treatment                  | TH  |
| Ambient air temperature for storage   | -40...70 °C   |
| Ambient air temperature for operation | -25...70 °C   |
| Overvoltage category                  | Class II conforming to IEC 60536  |
| IP degree of protection               | IP20 (rear face) conforming to IEC 60529<br>IP65 (front face) conforming to IEC 60529           |
| NEMA degree of protection             | NEMA 4 conforming to UL 50 E<br>NEMA 12 conforming to UL 50 E                                   |
| Standards                             | EN/IEC 60947-5-1<br>EN/IEC 60947-1<br>UL 508<br>JIS C8201-5-1<br>CSA C22.2 No 14<br>JIS C8201-1 |
| Vibration resistance                  | 5 gn (f= 2...500 Hz) conforming to IEC 60068-2-6  |
| Shock resistance                      | 50 gn (duration = 11 ms) for half sine wave acceleration conforming to IEC 60068-2-27           |
| Electromagnetic compatibility         | Disturbing field emission class B conforming to EN 55011  |

## Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Height             | 6 cm     |
| Package 1 Width              | 10 cm    |
| Package 1 Length             | 15 cm    |
| Package 1 Weight             | 19 g     |
| Unit Type of Package 2       | BAG      |
| Number of Units in Package 2 | 10       |
| Package 2 Height             | 6 cm     |
| Package 2 Width              | 10 cm    |
| Package 2 Length             | 15 cm    |
| Package 2 Weight             | 199 g    |
| Unit Type of Package 3       | S01      |
| Number of Units in Package 3 | 100      |
| Package 3 Height             | 15 cm    |
| Package 3 Width              | 15 cm    |
| Package 3 Length             | 40 cm    |
| Package 3 Weight             | 2.263 kg |

## Offer Sustainability

|                            |  |
|----------------------------|--|
| Sustainable offer status   | Green Premium product  |
| REACH Regulation           |  <a href="#">REACH Declaration</a>  |
| REACH free of SVHC         | Yes  |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope)  <a href="#">EU RoHS Declaration</a> |
| Toxic heavy metal free     | Yes  |
| Mercury free               | Yes  |
| China RoHS Regulation      |  <a href="#">China RoHS Declaration</a>   |
| RoHS exemption information |  <a href="#">Yes</a>  |
| Environmental Disclosure   |  <a href="#">Product Environmental Profile</a>  |
| Circularity Profile        |  <a href="#">End Of Life Information</a>  |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins  |

Contractual warranty


|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

---

Pilot Light with Screw Terminal

---

Dimensions



e Support panel thickness: 1 to 6 mm/0.4 to 0.24 in. (metal), 2 to 6 mm/0.8 to 0.24 in. (plastic).


## Mounting

### Diameter of Finished Fixing Holes




- (1) Minimum value.
- (2) 40 mm/1.58 in. for Emergency switching off pushbutton only.
- (3) Standard value:  $\varnothing 22.3$  (0; + 0.4) mm/ $\varnothing 0.88$  (0; + 0.02) in.

### Faston Clip Connection



### "U" Type Tag Connection



- (1) 6.5 mm/0.26 in. recommended, 7 mm/0.28 in. max.
- (2) M3 screw clamp terminal.

---

Wiring Diagram

---

